

DIN EN 16272-4:2016-12 (E)

Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Test method for determining the acoustic performance - Part 4: Intrinsic characteristics - In situ values of sound diffraction under direct sound field

Contents		Page
	European foreword	4
	Introduction	5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Symbols and abbreviations	9
5	Sound diffraction index difference measurements	10
5.1	General principle	10
5.2	Dimensions and specifications	15
5.2.1	Added devices	15
5.2.2	Reference walls	15
5.2.3	In situ tests	16
5.3	Positions of the sound source	16
5.4	Position of the microphone(s)	16
5.5	Free-field measurements	17
5.6	Measured quantity	18
5.7	Measuring equipment	18
5.7.1	Components of the measuring system	18
5.7.2	Sound source	20
5.7.3	Test signal	20
5.8	Data processing	20
5.8.1	Calibration	20
5.8.2	Sample rate	21
5.8.3	Background noise	21
5.8.4	Measurement points	21
5.8.5	Adrienne temporal window	21
5.8.6	Placement of the Adrienne temporal window	22
5.8.7	Low frequency limit and sample size	24
5.9	Positioning of the measuring equipment	24
5.9.1	Selection of the measurement positions	24
5.9.2	Reflecting objects	25
5.9.3	Safety considerations	25
5.10	Sound diffraction index difference	25
5.11	Sample surface and meteorological conditions	25
5.11.1	Condition of the sample surface	25
5.11.2	Wind	26
5.11.3	Air temperature	26
6	Measurement uncertainty	26
7	Measuring procedure	26
8	Test report	27

8.1	Expression of results	27
8.2	Further information	27
Annex A (informative) Indoor measurements for product qualification		29
A.1	General	29
A.2	Parasitic reflections	29
A.3	Reverberation time of the room	29
Annex B (informative) Measurement uncertainty		30
B.1	General	30
B.2	Expression for the calculation of sound diffraction index	30
B.3	Contributions to measurement uncertainty	31
B.4	Expanded uncertainty of measurement	32
B.5	Measurement uncertainty based upon reproducibility data	32
Bibliography		33