DIN EN 14033-2:2017-10 (E)

Railway applications - Track - Railbound construction and maintenance machines - Part 2: Technical requireme nts for travelling and working

Contents

Page

European foreword 7

Introduction 9

1 Scope 10
1.1 General 10
1.2 Validity of this European Standard 11

2 Normative references 11

3 Terms and definitions 12

4 Field of use of machines 13

5 Specific railway requirements and/or measures 13
5.1 Interaction with the Infrastructure 13
5.1.1 General 13
5.1.2 Stress induced into the rails 13
5.1.3 Auxiliary wheels, auxiliary guides and working parts 14
5.1.4 Maximum wheel loads 15
5.1.5 Loads applied to the ballast 17
5.1.6 Loads applied to the formation 17
5.1.7 Loads on structures 17
5.2 Stability and safety against derailment 18
5.2.1 Proof of overturning stability, machine stationary 18
5.2.2 Prevention of derailment in travelling mode 20
5.2.3 Prevention of derailment during working movements 20
5.3 Machine gauge 23
5.3.1 Stowing of moveable machine parts in travelling mode 23
5.3.2 Working gauge 24
5.3.3 Exceedance of gauge in working mode 25
5.4 Working places 25
5.4.1 General 25
5.4.2 Arrangement of working places 25
5.4.3 Work positions - Visibility 25
5.4.4 Cabin windows used solely for working 25
5.5 Access to working places 26
5.5.1 General 26
5.5.2 Access to working places 26
5.6 Influences on the environment 26
5.6.1 Exhaust gases 26
5.6.2 Noise levels outside the machine 26
5.7 Electromagnetic compatibility 26
5.8 Protection from risks due to electric traction equipment 26
5.8.1 General 26
5.8.2 Protection from live overhead lines 26
5.8.3 Minimum safety distance between machine parts and overhead line equipment. 27
5.8.4 Minimum safety distance between machine parts and conductor rail 27
5.8.5 Special earthing devices and/or protection from return traction currents 28
5.8.6 Use of a pantograph for other than traction use 28
5.9 Protection from the risks of fire 28

5.9.1 Material requirements ... 28
5.9.2 Fire detection and extinguishing systems ... 28
5.9.3 Fire extinguishing outside of the machine ... 28
5.10 Lighting for work ... 28
5.11 Visibility of machines ... 28
5.11.1 Marker lights for warning in travelling mode ... 28
5.11.2 Additional marker lights ... 29
5.12 Braking ... 29
5.12.1 General ... 29
5.12.2 Stopping distances ... 29
5.12.3 Holding on gradients ... 30
5.13 Warning systems ... 30
5.13.1 System for warning personnel of traffic on adjacent tracks ... 30
5.13.2 System for warning in travelling mode ... 31
5.14 Recovery conditions ... 31
5.15 Data recording ... 31
5.16 Parameters which influence ground based systems ... 31
5.17 Traction equipment ... 31
5.18 Laser equipment ... 32
5.19 Remote control ... 32

6 Verification of the conformity to the requirements and/or particular safety measures ... 32
6.1 General ... 32
6.2 Methods of testing ... 32
6.2.1 General ... 32
6.2.2 Visual check ... 32
6.2.3 Measurement ... 32
6.2.4 Functional test ... 33
6.2.5 Load test(s) ... 33
6.2.6 Specific verification/measurements ... 33

7 User information ... 33
7.1 General ... 33
7.1.1 Instructions ... 33
7.1.2 Special operating instructions ... 33
7.1.3 Maintenance instructions ... 35
7.2 Warning signs and pictograms ... 35

8 Marking of machines ... 35

Annex A (normative) Special national conditions ... 36

Annex B (normative) Check list for conformity ... 41

Annex C (normative) Warning plate ... 43

Annex D (informative) Working gauge ... 44

D.1 General ... 44
D.1.1 Introduction ... 44
D.1.2 Scope ... 44
D.1.3 List of symbols used ... 44
D.2 Determination of the horizontal working limit ... 47
D.2.1 General ... 47
D.2.2 Characteristics of the working track and the machine ... 48
D.2.3 Characteristics of a standard vehicle travelling on the adjacent line in service ... 48
D.3 Calculation of the reductions for the limit line of Figure D.2, applicable to the critical parts of the machine ... 48
D.4 Determination of clearance of the working parts ... 49
D.4.1 General ... 49
D.4.2 Method of calculation ... 50
D.4.3 Addition for curvature, for working parts (Zb) ... 50

D.4.4 Addition for cant (Zu) 50
D.4.5 Addition for safety (zs) 50
D.4.6 Kinematic clearance necessary for a standard vehicle on the track in service (RBk) 51
D.4.7 Possible exterior clearance for a working part (AWz) 51

Annex E (normative) Technical documentation 57

E.1 General 57
E.2 General notices on the machine 57
E.3 Assembly drawing indicating the following: 57
E.4 Detailed drawings indicating the following: 57
E.5 Detailed drawings with the following indications 57
E.6 Technical details 58
E.7 Possible functions of the working parts 58

Annex F (normative) Limiting geometric parameters of the degraded working track 59

Annex G (normative) Pictograms -- Pictogram "Working direction" 60

Annex H (informative) Method of calculating safety against derailment 61

H.1 Calculation of the safety against derailment 61
H.1.1 General 61
H.1.2 Calculation of the vehicle testing twist 62
H.1.3 Limit value of the safety against derailment 62
H.1.4 Guiding force and vertical wheel-load of the leading wheel 63
H.1.5 Guiding force and vertical wheel-load of the leading wheel in the working load case 63
H.1.6 Calculation of the torsional stiffness of the vehicle 64

Annex I (informative) Procedure for working authorization 67

I.1 General 67
I.2 Validity and application of the authorization to work 67
I.2.1 Validity 67
I.2.2 Field of application 67
I.2.3 Enlargement of field of application 67
I.2.4 Withdrawal of the authorization to work 67
I.2.5 Renewal of the authorization to work 67
I.3 Applications for authorization to work 68
I.4 Submission of the technical documentation 68
I.5 Type testing 68
I.6 Quality testing 68
I.7 Type approval 68
I.8 Examining the finished machine 69
I.9 Authorization to work for machines identical to a machine that has received type approval 69
I.10 Refusal of working authorization 69
I.11 Validity of working authorization 69
I.12 Procedure for working agreement 70

Annex J (informative) Basis of calculations 71

J.1 Machines without load control devices 71
J.2 Machines with load control devices 71

Annex K (informative) Instruction handbook 72

Annex L (normative) Design specification for earthing pantograph(s) where permitted on individual infrastructures 74

L.1 Object 74
L.2 Position of the pantograph 75

L.3 Maintaining contact between the equipotential contact strip and the contact wire75 L.4 Contact strip design 75
L.5 Electrical connection between the equipotential pantograph head and the rail 75

Annex M (informative) Structure of European Standards for track construction and maintenance machines 77

Bibliography 79

Tables Table 1 -- Stress limit in the rails 14

Table 2 -- Maximum wheel load with the machine in travelling and working mode for machines without wheel load control devices 16

Table 3 --Maximum wheel load with the machine in working and travelling mode for machine that do not lift a load or machine that lift a load with wheel load control devices 17

Table 4 -- Load cases for calculating stability 19

Table 5 -- Load cases for testing prevention of overturning 20

Table 6 -- Comparison of track parameters 21

Table 7 -- Minimum safety distance between machine parts and overhead line equipment27 Table 8 -- Minimum safety distance between machine parts and conductor rails 27

Table 9 -- Maximum stopping distances 30

Table A.1 -- Special national conditions 39

Table B.1 -- Determination of safety requirements and/or safety measures 41

Table F.1 -- Limiting geometric parameters of the degraded working track 59

Table M.1 -- Structure of European Standards for track construction and maintenance machines ... 78

Figures Figure 1 -- Cross section of rail showing stress points given in Table 1 14

Figure C.1 -- Warning plate 43

Figure C.2 -- Example of general warning sign 43

Figure D.1 -- Position of working zones and the zone limit between the working track and the adjacent operating track 47

Figure D.2 -- Lateral working limit 49

Figure D.3 -- Kinematic envelope necessary for a G1 or G2 gauge vehicle on a line open to traffic on a curve of a radius 250 m R < 2 000 m 53

Figure D.4 -- Kinematic space "RBk" necessary for a G1 or G2 gauge standard vehicle on the operating track on a curve of with radius 2 000 m R < 4 000 m 54

Figure D.5 -- Kinematic space "RBk" necessary for a G1 or G2 gauge vehicle on the operating track on a curve of with radius R 4 000 m 55

Figure D.6 -- Representation of calculating variants of the permissible working distance AWz 56

Figure G.1 -- Example of pictograms denoting working directions 60

Figure I.1 -- Procedure for working agreement 70

Figure L.1 --Principle of equipotential bonding (example) 74

Figure L.2 --Contact strip freedom of movement - Example of an equipotential pantograph 75

Figure M.1 -- Flowchart of European Standards for track construction and maintenance machines ..77