

DIN EN 14033-2:2017-10 (E)

Railway applications - Track - Railbound construction and maintenance machines - Part 2: Technical requirements for travelling and working

Contents		Page
European foreword		7
Introduction		9
1	Scope	10
1.1	General	10
1.2	Validity of this European Standard	11
2	Normative references	11
3	Terms and definitions	12
4	Field of use of machines	13
5	Specific railway requirements and/or measures	13
5.1	Interaction with the Infrastructure	13
5.1.1	General	13
5.1.2	Stress induced into the rails	13
5.1.3	Auxiliary wheels, auxiliary guides and working parts	14
5.1.4	Maximum wheel loads	15
5.1.5	Loads applied to the ballast	17
5.1.6	Loads applied to the formation	17
5.1.7	Loads on structures	17
5.2	Stability and safety against derailment	18
5.2.1	Proof of overturning stability, machine stationary	18
5.2.2	Prevention of derailment in travelling mode	20
5.2.3	Prevention of derailment during working movements	20
5.3	Machine gauge	23
5.3.1	Stowing of moveable machine parts in travelling mode	23
5.3.2	Working gauge	24
5.3.3	Exceedance of gauge in working mode	25
5.4	Working places	25
5.4.1	General	25
5.4.2	Arrangement of working places	25
5.4.3	Work positions - Visibility	25
5.4.4	Cabin windows used solely for working	25
5.5	Access to working places	26
5.5.1	General	26
5.5.2	Access to working places	26
5.6	Influences on the environment	26
5.6.1	Exhaust gases	26
5.6.2	Noise levels outside the machine	26
5.7	Electromagnetic compatibility	26
5.8	Protection from risks due to electric traction equipment	26
5.8.1	General	26
5.8.2	Protection from live overhead lines	26
5.8.3	Minimum safety distance between machine parts and overhead line equipment.	27
5.8.4	Minimum safety distance between machine parts and conductor rail	27
5.8.5	Special earthing devices and/or protection from return traction currents	28
5.8.6	Use of a pantograph for other than traction use	28
5.9	Protection from the risks of fire	28

5.9.1	Material requirements	28
5.9.2	Fire detection and extinguishing systems	28
5.9.3	Fire extinguishing outside of the machine	28
5.10	Lighting for work	28
5.11	Visibility of machines	28
5.11.1	Marker lights for warning in travelling mode	28
5.11.2	Additional marker lights	29
5.12	Braking	29
5.12.1	General	29
5.12.2	Stopping distances	29
5.12.3	Holding on gradients	30
5.13	Warning systems	30
5.13.1	System for warning personnel of traffic on adjacent tracks	30
5.13.2	System for warning in travelling mode	31
5.14	Recovery conditions	31
5.15	Data recording	31
5.16	Parameters which influence ground based systems	31
5.17	Traction equipment	31
5.18	Laser equipment	32
5.19	Remote control	32
6	Verification of the conformity to the requirements and/or particular safety measures	32
6.1	General	32
6.2	Methods of testing	32
6.2.1	General	32
6.2.2	Visual check	32
6.2.3	Measurement	32
6.2.4	Functional test	33
6.2.5	Load test(s)	33
6.2.6	Specific verification/measurements	33
7	User information	33
7.1	General	33
7.1.1	Instructions	33
7.1.2	Special operating instructions	33
7.1.3	Maintenance instructions	35
7.2	Warning signs and pictograms	35
8	Marking of machines	35
Annex A (normative) Special national conditions		36
Annex B (normative) Check list for conformity		41
Annex C (normative) Warning plate		43
Annex D (informative) Working gauge		44
D.1	General	44
D.1.1	Introduction	44
D.1.2	Scope	44
D.1.3	List of symbols used	44
D.2	Determination of the horizontal working limit	47
D.2.1	General	47
D.2.2	Characteristics of the working track and the machine	48
D.2.3	Characteristics of a standard vehicle travelling on the adjacent line in service	48
D.3	Calculation of the reductions for the limit line of Figure D.2, applicable to the critical parts of the machine	48
D.4	Determination of clearance of the working parts	49
D.4.1	General	49
D.4.2	Method of calculation	50
D.4.3	Addition for curvature, for working parts (Zb)	50

D.4.4	Addition for cant (Zu)	50
D.4.5	Addition for safety (zs)	50
D.4.6	Kinematic clearance necessary for a standard vehicle on the track in service (RBk)51	
D.4.7	Possible exterior clearance for a working part (AWz)	51
Annex E (normative) Technical documentation		57
E.1	General	57
E.2	General notices on the machine	57
E.3	Assembly drawing indicating the following:	57
E.4	Detailed drawings indicating the following:	57
E.5	Detailed drawings with the following indications	57
E.6	Technical details	58
E.7	Possible functions of the working parts	58
Annex F (normative) Limiting geometric parameters of the degraded working track		59
Annex G (normative) Pictograms -- Pictogram "Working direction"		60
Annex H (informative) Method of calculating safety against derailment		61
H.1	Calculation of the safety against derailment	61
H.1.1	General	61
H.1.2	Calculation of the vehicle testing twist	62
H.1.3	Limit value of the safety against derailment	62
H.1.4	Guiding force and vertical wheel-load of the leading wheel	63
H.1.5	Guiding force and vertical wheel-load of the leading wheel in the working load case	63
H.1.6	Calculation of the torsional stiffness of the vehicle	64
Annex I (informative) Procedure for working authorization		67
I.1	General	67
I.2	Validity and application of the authorization to work	67
I.2.1	Validity	67
I.2.2	Field of application	67
I.2.3	Enlargement of field of application	67
I.2.4	Withdrawal of the authorization to work	67
I.2.5	Renewal of the authorization to work	67
I.3	Applications for authorization to work	68
I.4	Submission of the technical documentation	68
I.5	Type testing	68
I.6	Quality testing	68
I.7	Type approval	68
I.8	Examining the finished machine	69
I.9	Authorization to work for machines identical to a machine that has received type approval	69
I.10	Refusal of working authorization	69
I.11	Validity of working authorization	69
I.12	Procedure for working agreement	70
Annex J (informative) Basis of calculations		71
J.1	Machines without load control devices	71
J.2	Machines with load control devices	71
Annex K (informative) Instruction handbook		72
Annex L (normative) Design specification for earthing pantograph(s) where permitted on individual infrastructures		74
L.1	Object	74
L.2	Position of the pantograph	75

L.3	Maintaining contact between the equipotential contact strip and the contact wire	75
	Contact strip design	75
L.5	Electrical connection between the equipotential pantograph head and the rail	75
Annex M (informative) Structure of European Standards for track construction and maintenance machines		77
Bibliography		79
Tables	Table 1 -- Stress limit in the rails	14
	Table 2 -- Maximum wheel load with the machine in travelling and working mode for machines without wheel load control devices	16
	Table 3 -- Maximum wheel load with the machine in working and travelling mode for machine that do not lift a load or machine that lift a load with wheel load control devices	17
	Table 4 -- Load cases for calculating stability	19
	Table 5 -- Load cases for testing prevention of overturning	20
	Table 6 -- Comparison of track parameters	21
	Table 7 -- Minimum safety distance between machine parts and overhead line equipment	27
	-- Minimum safety distance between machine parts and conductor rails	27
	Table 9 -- Maximum stopping distances	30
	Table A.1 -- Special national conditions	39
	Table B.1 -- Determination of safety requirements and/or safety measures	41
	Table F.1 -- Limiting geometric parameters of the degraded working track	59
	Table M.1 -- Structure of European Standards for track construction and maintenance machines ...	78
Figures	Figure 1 -- Cross section of rail showing stress points given in Table 1	14
	Figure C.1 -- Warning plate	43
	Figure C.2 -- Example of general warning sign	43
	Figure D.1 -- Position of working zones and the zone limit between the working track and the adjacent operating track	47
	Figure D.2 -- Lateral working limit	49
	Figure D.3 -- Kinematic envelope necessary for a G1 or G2 gauge vehicle on a line open to traffic on a curve of a radius 250 m $R < 2\,000$ m	53
	Figure D.4 -- Kinematic space "RBk" necessary for a G1 or G2 gauge standard vehicle on the operating track on a curve of with radius 2 000 m $R < 4\,000$ m	54
	Figure D.5 -- Kinematic space "RBk" necessary for a G1 or G2 gauge vehicle on the operating track on a curve of with radius $R \geq 4\,000$ m	55
	Figure D.6 -- Representation of calculating variants of the permissible working distance AWz	56
	Figure G.1 -- Example of pictograms denoting working directions	60
	Figure I.1 -- Procedure for working agreement	70

Figure L.1 --Principle of equipotential bonding (example)74
Figure L.2 --Contact strip freedom of movement - Example of an equipotential pantograph 75
Figure M.1 -- Flowchart of European Standards for track construction and maintenance machines ..77