DIN EN 13803:2017-09 (E)

Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

Contents

Page

European foreword 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Symbols and abbreviations 10

5 General 11
5.1 Background 11
5.2 Alignment characteristics 11

6 Limits for 1 435 mm gauge 13
6.1 Radius of horizontal curve R 13
6.2 Cant D 13
6.3 Cant deficiency I 14
6.4 Cant excess E 16
6.5 Length of cant transitions LD and transition curves in the horizontal plane LK 17
6.5.1 General 17
6.5.2 Lengths of linear cant transitions and clothoids 17
6.5.3 Lengths of transition curves with non-constant gradient of curvature and cant 18
6.6 Cant gradient dD/ds 19
6.7 Rate of change of cant dD/dt 19
6.8 Rate of change of cant deficiency dI/dt 20
6.9 Length of constant cant between two linear cant transitions Li 21
6.10 Abrupt change of horizontal curvature 22
6.11 Abrupt change of cant deficiency I 22
6.12 Length between two abrupt changes of horizontal curvature Lc 22
6.13 Length between two abrupt changes of cant deficiency Ls 23
6.14 Track gradients p 24
6.15 Vertical radius Rv 25
6.16 Length of vertical curves Lv 25
6.17 Abrupt change of track gradient p 26

Annex A (normative) Rules for converting parameter values for track gauges wider than 1 435 mm . 27

A.1 Scope 27
A.2 Symbols and abbreviations 27
A.3 Basic assumptions and equivalence rules 29
A.3.1 General 29
A.3.2 Basic formulae 29
A.3.3 Basic data 30
A.4 Detailed conversion rules 30
A.4.1 General 30
A.4.2 Cant D1 (Subclause 6.2 of the main body of the standard) 30
A.4.3 Cant deficiency I1 (Subclause 6.3 of the main body of the standard) 32
A.4.4 Cant excess E1 (Subclause 6.4 of the main body of the standard) 33
A.4.5 Lengths of cant transitions LD and transition curves in the horizontal plane LK (Subclause 6.5 of the main body of the standard) 33

A.4.6 Cant gradient dD1/ds (Subclause 6.6 of the main body of the standard) 34
A.4.7 Rate of change of cant dD1/dt (Subclause 6.7 of the main body of the standard) 34
A.4.8 Rate of change of cant deficiency dI1/dt (Subclause 6.8 of the main body of the standard) 35
A.4.9 Abrupt change of curvature and abrupt change of cant deficiency I1 (Subclauses 6.10 and 6.11 of the main body of the standard) 36
A.4.10 Other parameters (Subclauses 6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16 and 6.17 of the main body of the standard) 36

Annex B (normative) Track alignment design parameter limits for track gauges wider than 1 435 mm 37

B.1 Scope 37
B.2 Requirements for a gauge of 1 520 mm and 1 524 mm 37
B.2.1 General 37
B.2.2 Radius of horizontal curve R1 37
B.2.3 Cant D1 37
B.2.4 Cant deficiency I1 38
B.2.5 Cant excess E1 39
B.2.6 Length of cant transitions LD1 and transition curves in the horizontal plane LK1 39
B.2.7 Cant gradient dD1/ds 40
B.2.8 Rate of change of cant dD1/dt 41
B.2.9 Rate of change of cant deficiency dI1/dt 41
B.2.10 Length of constant cant between two linear cant transitions Li1 42
B.2.11 Abrupt change of horizontal curvature 43
B.2.12 Abrupt change of cant deficiency I1 43
B.2.13 Length between two abrupt changes of horizontal curvature LC1 43
B.2.14 Length between two abrupt changes of cant deficiency Ls1 43
B.2.15 Track gradients p1 44
B.2.16 Vertical radius Rv1 44
B.2.17 Length vertical curves Lv1 44
B.2.18 Abrupt change of track gradient p1 44
B.3 Requirements for a gauge of 1 668 mm 44
B.3.1 General 44
B.3.2 Radius of horizontal curve R1 44
B.3.3 Cant D1 44
B.3.4 Cant deficiency I1 45
B.3.5 Cant excess E1 46
B.3.6 Length of cant transitions LD1 and transition curves in the horizontal plane LK1 46
B.3.7 Cant gradient dD1/ds 47
B.3.8 Rate of change of cant dD1/dt 48
B.3.9 Rate of change of cant deficiency dI1/dt 49
B.3.10 Length of constant cant between two linear cant transitions Li1 50
B.3.11 Abrupt change of horizontal curvature 50
B.3.12 Abrupt change of cant deficiency I1 50
B.3.13 Length between two abrupt changes of horizontal curvature LC1 51
B.3.14 Length between two abrupt changes of cant deficiency Ls1 51
B.3.15 Track gradients p1 51
B.3.16 Vertical radius Rv1 51
B.3.17 Length vertical curves Lv1 52
B.3.18 Abrupt change of track gradient p1 52

Annex C (informative) Supplementary information about shape and length of transition curves 53

C.1 General 53
C.2 Definitions and properties of different transition curves and cant transitions 53
C.2.1 Definitions 53
C.2.2 Properties 54
C.3 Further aspects that may be considered for a progressive track alignment design 59
C.3.1 Background 59
C.3.2 Progressive track alignment design 59

Annex D (informative) Constraints and risks associated with the use of exceptional limits 62

Annex E (informative) Evaluation of conditions at the toe of a switch 63

E.1 General 63
E.2 Method based on effective radius 63

Annex F (informative) Design considerations for switch and crossing units 65

F.1 Examples of common switch and crossing units 65
F.2 Use of diamond crossings, diamond crossings with slips and tandem turnouts 67
F.3 Switch and crossing units on, or near, under-bridges 67
F.4 Abutting switch and crossing units 67
F.5 Switch and crossing units on horizontal curves 67
F.6 Switch and crossing units on canted track 68
F.7 Vertical alignments and switch and crossing units 68

Annex G (informative) Examples of applications 71

G.1 General 71
G.2 Example of crossover on horizontal curve 71
G.3 Example of bi-linear cant transition 72
G.4 Example where a cant transition is designed without a coinciding transition curve 73
G.5 Example of substandard transition curve 74
G.6 Example where several alignment elements forms an intermediate length 75

Annex H (informative) Examples of local limits for cant deficiency 76

Annex I (informative) Considerations regarding cant deficiency and cant excess 77

I.1 Introduction 77
I.2 Cant deficiency 77
I.3 Cant excess 77
I.4 Wheel climb criterion 77
I.5 Vehicle overturning 78
I.6 The lateral strength of a track under loading (Prud'homme limit) 78
I.7 Cant deficiency at switch and crossing layouts on curves 78

Annex J (informative) Passenger comfort on curves 79

J.1 General 79
J.2 Lateral acceleration 79
J.3 Lateral jerk 79
J.3.1 Lateral jerk as a function of rate of change of cant deficiency 79
J.3.2 Lateral jerk as a function of an abrupt change of cant deficiency 80
J.4 Roll motions 80

Annex K (normative) Sign rules for calculation of D, I and p 81

K.1 General regarding the sign rules 81
K.2 Sign rules for calculation of D 81
K.3 Sign rules for calculation of I 81
K.4 Sign rules for calculation of p 82

Annex L (informative) Length of constant cant between two linear cant transitions Li 84

Annex M (informative) The principle of virtual transition 85

M.1 Virtual transition at an abrupt change of cant deficiency 85
M.2 Virtual transition at a short intermediate length between two abrupt changes of cant deficiency 86
M.3 Limits based on the principle of the virtual transition 87

M.3.1 General 87
M.3.2 Characteristic vehicle with a distance of 20 m between bogie centres 87
M.3.3 Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres 87

Annex N (normative) Lengths of intermediate elements Lc to prevent buffer locking 89

N.1 General 89
N.2 Basic vehicles and running conditions 89
N.3 Lengths Lc of an intermediate straight track between two long circular curves in the opposite directions 89
N.4 General cases for end throw differences 90

Annex O (informative) Considerations for track gradients 93

O.1 Uphill gradients 93
O.2 Downhill gradients 93
O.3 Gradients for stabling tracks and at platforms 93

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC 94

Bibliography 97