

DIN EN 13803:2017-09 (E)

Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

Contents		Page
European foreword		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Symbols and abbreviations	10
5	General	11
5.1	Background	11
5.2	Alignment characteristics	11
6	Limits for 1 435 mm gauge	13
6.1	Radius of horizontal curve R	13
6.2	Cant D	13
6.3	Cant deficiency I	14
6.4	Cant excess E	16
6.5	Length of cant transitions LD and transition curves in the horizontal plane LK	17
6.5.1	General	17
6.5.2	Lengths of linear cant transitions and clothoids	17
6.5.3	Lengths of transition curves with non-constant gradient of curvature and cant	18
6.6	Cant gradient dD/ds	19
6.7	Rate of change of cant dD/dt	19
6.8	Rate of change of cant deficiency dl/dt	20
6.9	Length of constant cant between two linear cant transitions Li	21
6.10	Abrupt change of horizontal curvature	22
6.11	Abrupt change of cant deficiency I	22
6.12	Length between two abrupt changes of horizontal curvature Lc	22
6.13	Length between two abrupt changes of cant deficiency Ls	23
6.14	Track gradients p	24
6.15	Vertical radius Rv	25
6.16	Length of vertical curves Lv	25
6.17	Abrupt change of track gradient p	26
Annex A (normative) Rules for converting parameter values for track gauges wider than 1 435 mm .27		
A.1	Scope	27
A.2	Symbols and abbreviations	27
A.3	Basic assumptions and equivalence rules	29
A.3.1	General	29
A.3.2	Basic formulae	29
A.3.3	Basic data	30
A.4	Detailed conversion rules	30
A.4.1	General	30
A.4.2	Cant D1 (Subclause 6.2 of the main body of the standard)	30
A.4.3	Cant deficiency I1 (Subclause 6.3 of the main body of the standard)	32
A.4.4	Cant excess E1 (Subclause 6.4 of the main body of the standard)	33
A.4.5	Lengths of cant transitions LD and transition curves in the horizontal plane LK (Subclause 6.5 of the main body of the standard)	33

A.4.6	Cant gradient $dD1/ds$ (Subclause 6.6 of the main body of the standard)	34
A.4.7	Rate of change of cant $dD1/dt$ (Subclause 6.7 of the main body of the standard)	34
A.4.8	Rate of change of cant deficiency $dI1/dt$ (Subclause 6.8 of the main body of the standard)	35
A.4.9	Abrupt change of curvature and abrupt change of cant deficiency $I1$ (Subclauses 6.10 and 6.11 of the main body of the standard)	36
A.4.10	Other parameters (Subclauses 6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16 and 6.17 of the main body of the standard)	36

Annex B (normative) Track alignment design parameter limits for track gauges wider than 1 435 mm 37

B.1	Scope	37
B.2	Requirements for a gauge of 1 520 mm and 1 524 mm	37
B.2.1	General	37
B.2.2	Radius of horizontal curve $R1$	37
B.2.3	Cant $D1$	37
B.2.4	Cant deficiency $I1$	38
B.2.5	Cant excess $E1$	39
B.2.6	Length of cant transitions $LD1$ and transition curves in the horizontal plane $LK1$	39
B.2.7	Cant gradient $dD1/ds$	40
B.2.8	Rate of change of cant $dD1/dt$	41
B.2.9	Rate of change of cant deficiency $dI1/dt$	41
B.2.10	Length of constant cant between two linear cant transitions $Li1$	42
B.2.11	Abrupt change of horizontal curvature	43
B.2.12	Abrupt change of cant deficiency $I1$	43
B.2.13	Length between two abrupt changes of horizontal curvature $LC1$	43
B.2.14	Length between two abrupt changes of cant deficiency $Ls1$	43
B.2.15	Track gradients $p1$	44
B.2.16	Vertical radius $Rv1$	44
B.2.17	Length vertical curves $Lv1$	44
B.2.18	Abrupt change of track gradient $p1$	44
B.3	Requirements for a gauge of 1 668 mm	44
B.3.1	General	44
B.3.2	Radius of horizontal curve $R1$	44
B.3.3	Cant $D1$	44
B.3.4	Cant deficiency $I1$	45
B.3.5	Cant excess $E1$	46
B.3.6	Length of cant transitions $LD1$ and transition curves in the horizontal plane $LK1$	46
B.3.7	Cant gradient $dD1/ds$	47
B.3.8	Rate of change of cant $dD1/dt$	48
B.3.9	Rate of change of cant deficiency $dI1/dt$	49
B.3.10	Length of constant cant between two linear cant transitions $Li1$	50
B.3.11	Abrupt change of horizontal curvature	50
B.3.12	Abrupt change of cant deficiency $I1$	50
B.3.13	Length between two abrupt changes of horizontal curvature $LC1$	51
B.3.14	Length between two abrupt changes of cant deficiency $Ls1$	51
B.3.15	Track gradients $p1$	51
B.3.16	Vertical radius $Rv1$	51
B.3.17	Length vertical curves $Lv1$	52
B.3.18	Abrupt change of track gradient $p1$	52

Annex C (informative) Supplementary information about shape and length of transition curves 53

C.1	General	53
C.2	Definitions and properties of different transition curves and cant transitions	53
C.2.1	Definitions	53
C.2.2	Properties	54
C.3	Further aspects that may be considered for a progressive track alignment design	59
C.3.1	Background	59
C.3.2	Progressive track alignment design	59

Annex D (informative) Constraints and risks associated with the use of exceptional limits	62
Annex E (informative) Evaluation of conditions at the toe of a switch	63
E.1 General	63
E.2 Method based on effective radius	63
Annex F (informative) Design considerations for switch and crossing units	65
F.1 Examples of common switch and crossing units	65
F.2 Use of diamond crossings, diamond crossings with slips and tandem turnouts	67
F.3 Switch and crossing units on, or near, under-bridges	67
F.4 Abutting switch and crossing units	67
F.5 Switch and crossing units on horizontal curves	67
F.6 Switch and crossing units on canted track	68
F.7 Vertical alignments and switch and crossing units	68
Annex G (informative) Examples of applications	71
G.1 General	71
G.2 Example of crossover on horizontal curve	71
G.3 Example of bi-linear cant transition	72
G.4 Example where a cant transition is designed without a coinciding transition curve	73
G.5 Example of substandard transition curve	74
G.6 Example where several alignment elements forms an intermediate length	75
Annex H (informative) Examples of local limits for cant deficiency	76
Annex I (informative) Considerations regarding cant deficiency and cant excess	77
I.1 Introduction	77
I.2 Cant deficiency	77
I.3 Cant excess	77
I.4 Wheel climb criterion	77
I.5 Vehicle overturning	78
I.6 The lateral strength of a track under loading (Prud'homme limit)	78
I.7 Cant deficiency at switch and crossing layouts on curves	78
Annex J (informative) Passenger comfort on curves	79
J.1 General	79
J.2 Lateral acceleration	79
J.3 Lateral jerk	79
J.3.1 Lateral jerk as a function of rate of change of cant deficiency	79
J.3.2 Lateral jerk as a function of an abrupt change of cant deficiency	80
J.4 Roll motions	80
Annex K (normative) Sign rules for calculation of D, I and p	81
K.1 General regarding the sign rules	81
K.2 Sign rules for calculation of D	81
K.3 Sign rules for calculation of I	81
K.4 Sign rules for calculation of p	82
Annex L (informative) Length of constant cant between two linear cant transitions Li	84
Annex M (informative) The principle of virtual transition	85
M.1 Virtual transition at an abrupt change of cant deficiency	85
M.2 Virtual transition at a short intermediate length between two abrupt changes of cant deficiency	86
M.3 Limits based on the principle of the virtual transition	87

M.3.1	General	87
M.3.2	Characteristic vehicle with a distance of 20 m between bogie centres	87
M.3.3	Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres	87
Annex N (normative) Lengths of intermediate elements Lc to prevent buffer locking		89
N.1	General	89
N.2	Basic vehicles and running conditions	89
N.3	Lengths Lc of an intermediate straight track between two long circular curves in the opposite directions	89
N.4	General cases for end throw differences	90
Annex O (informative) Considerations for track gradients		93
O.1	Uphill gradients	93
O.2	Downhill gradients	93
O.3	Gradients for stabling tracks and at platforms	93
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC		94
Bibliography		97