

# DIN EN 13803:2017-09 (E)

## Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| European foreword .....  |  | 6           |
| 1  | Scope .....  | 7           |
| 2  | Normative references .....   | 7           |
| 3  | Terms and definitions .....  | 7           |
| 4  | Symbols and abbreviations .....  | 10          |
| 5  | General .....  | 11          |
| 5.1  | Background .....   | 11          |
| 5.2  | Alignment characteristics .....  | 11          |
| 6  | Limits for 1 435 mm gauge .....  | 13          |
| 6.1  | Radius of horizontal curve R .....   | 13          |
| 6.2  | Cant D .....   | 13          |
| 6.3  | Cant deficiency I .....  | 14          |
| 6.4  | Cant excess E .....  | 16          |
| 6.5  | Length of cant transitions LD and transition curves in the horizontal plane LK .....   | 17          |
| 6.5.1  | General .....  | 17          |
| 6.5.2  | Lengths of linear cant transitions and clothoids .....   | 17          |
| 6.5.3  | Lengths of transition curves with non-constant gradient of curvature and cant .....  | 18          |
| 6.6  | Cant gradient $dD/ds$ .....  | 19          |
| 6.7  | Rate of change of cant $dD/dt$ .....   | 19          |
| 6.8  | Rate of change of cant deficiency $dI/dt$ .....  | 20          |
| 6.9  | Length of constant cant between two linear cant transitions $L_i$ .....  | 21          |
| 6.10   | Abrupt change of horizontal curvature .....  | 22          |
| 6.11   | Abrupt change of cant deficiency I .....   | 22          |
| 6.12   | Length between two abrupt changes of horizontal curvature $L_c$ .....  | 22          |
| 6.13   | Length between two abrupt changes of cant deficiency $L_s$ .....   | 23          |
| 6.14   | Track gradients p .....  | 24          |
| 6.15   | Vertical radius $R_v$ .....  | 25          |
| 6.16   | Length of vertical curves $L_v$ .....  | 25          |
| 6.17   | Abrupt change of track gradient p .....  | 26          |
| Annex A (normative) Rules for converting parameter values for track gauges wider than 1 435 mm ..... |  | 27          |
| A.1  | Scope .....  | 27          |
| A.2  | Symbols and abbreviations .....  | 27          |
| A.3  | Basic assumptions and equivalence rules .....  | 29          |
| A.3.1  | General .....  | 29          |
| A.3.2  | Basic formulae .....   | 29          |
| A.3.3  | Basic data .....   | 30          |
| A.4  | Detailed conversion rules .....  | 30          |
| A.4.1  | General .....  | 30          |
| A.4.2  | Cant D1 (Subclause 6.2 of the main body of the standard) .....   | 30          |
| A.4.3  | Cant deficiency I1 (Subclause 6.3 of the main body of the standard) .....  | 32          |
| A.4.4  | Cant excess E1 (Subclause 6.4 of the main body of the standard) .....  | 33          |
| A.4.5  | Lengths of cant transitions LD and transition curves in the horizontal plane LK (Subclause 6.5 of the main body of the standard) ..... | 33          |

|        |  |    |
|--------|--|----|
| A.4.6  | Cant gradient $dD1/ds$ (Subclause 6.6 of the main body of the standard)  | 34 |
| A.4.7  | Rate of change of cant $dD1/dt$ (Subclause 6.7 of the main body of the standard)   | 34 |
| A.4.8  | Rate of change of cant deficiency $dI1/dt$ (Subclause 6.8 of the main body of the standard)                                      | 35 |
| A.4.9  | Abrupt change of curvature and abrupt change of cant deficiency $I1$ (Subclauses 6.10 and 6.11 of the main body of the standard) | 36 |
| A.4.10 | Other parameters (Subclauses 6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16 and 6.17 of the main body of the standard)                   | 36 |

**Annex B (normative) Track alignment design parameter limits for track gauges wider than 1 435 mm** ..... 37

|        |  |    |
|--------|--|----|
| B.1    | Scope  | 37 |
| B.2    | Requirements for a gauge of 1 520 mm and 1 524 mm                                    | 37 |
| B.2.1  | General  | 37 |
| B.2.2  | Radius of horizontal curve $R1$  | 37 |
| B.2.3  | Cant $D1$  | 37 |
| B.2.4  | Cant deficiency $I1$   | 38 |
| B.2.5  | Cant excess $E1$   | 39 |
| B.2.6  | Length of cant transitions $LD1$ and transition curves in the horizontal plane $LK1$ | 39 |
| B.2.7  | Cant gradient $dD1/ds$   | 40 |
| B.2.8  | Rate of change of cant $dD1/dt$  | 41 |
| B.2.9  | Rate of change of cant deficiency $dI1/dt$   | 41 |
| B.2.10 | Length of constant cant between two linear cant transitions $Li1$                    | 42 |
| B.2.11 | Abrupt change of horizontal curvature  | 43 |
| B.2.12 | Abrupt change of cant deficiency $I1$  | 43 |
| B.2.13 | Length between two abrupt changes of horizontal curvature $LC1$                      | 43 |
| B.2.14 | Length between two abrupt changes of cant deficiency $Ls1$                           | 43 |
| B.2.15 | Track gradients $p1$   | 44 |
| B.2.16 | Vertical radius $Rv1$  | 44 |
| B.2.17 | Length vertical curves $Lv1$   | 44 |
| B.2.18 | Abrupt change of track gradient $p1$   | 44 |
| B.3    | Requirements for a gauge of 1 668 mm   | 44 |
| B.3.1  | General  | 44 |
| B.3.2  | Radius of horizontal curve $R1$  | 44 |
| B.3.3  | Cant $D1$  | 44 |
| B.3.4  | Cant deficiency $I1$   | 45 |
| B.3.5  | Cant excess $E1$   | 46 |
| B.3.6  | Length of cant transitions $LD1$ and transition curves in the horizontal plane $LK1$ | 46 |
| B.3.7  | Cant gradient $dD1/ds$   | 47 |
| B.3.8  | Rate of change of cant $dD1/dt$  | 48 |
| B.3.9  | Rate of change of cant deficiency $dI1/dt$   | 49 |
| B.3.10 | Length of constant cant between two linear cant transitions $Li1$                    | 50 |
| B.3.11 | Abrupt change of horizontal curvature  | 50 |
| B.3.12 | Abrupt change of cant deficiency $I1$  | 50 |
| B.3.13 | Length between two abrupt changes of horizontal curvature $LC1$                      | 51 |
| B.3.14 | Length between two abrupt changes of cant deficiency $Ls1$                           | 51 |
| B.3.15 | Track gradients $p1$   | 51 |
| B.3.16 | Vertical radius $Rv1$  | 51 |
| B.3.17 | Length vertical curves $Lv1$   | 52 |
| B.3.18 | Abrupt change of track gradient $p1$   | 52 |

**Annex C (informative) Supplementary information about shape and length of transition curves** ..... 53

|       |   |    |
|-------|---|----|
| C.1   | General   | 53 |
| C.2   | Definitions and properties of different transition curves and cant transitions  | 53 |
| C.2.1 | Definitions   | 53 |
| C.2.2 | Properties  | 54 |
| C.3   | Further aspects that may be considered for a progressive track alignment design | 59 |
| C.3.1 | Background  | 59 |
| C.3.2 | Progressive track alignment design  | 59 |

|  |           |
|--|-----------|
| <b>Annex D (informative) Constraints and risks associated with the use of exceptional limits .....</b>           | <b>62</b> |
| <b>Annex E (informative) Evaluation of conditions at the toe of a switch .....</b>                               | <b>63</b> |
| <b>E.1 General .....</b>   | <b>63</b> |
| <b>E.2 Method based on effective radius .....</b>  | <b>63</b> |
| <b>Annex F (informative) Design considerations for switch and crossing units .....</b>                           | <b>65</b> |
| <b>F.1 Examples of common switch and crossing units .....</b>  | <b>65</b> |
| <b>F.2 Use of diamond crossings, diamond crossings with slips and tandem turnouts .....</b>                      | <b>67</b> |
| <b>F.3 Switch and crossing units on, or near, under-bridges .....</b>  | <b>67</b> |
| <b>F.4 Abutting switch and crossing units .....</b>  | <b>67</b> |
| <b>F.5 Switch and crossing units on horizontal curves .....</b>  | <b>67</b> |
| <b>F.6 Switch and crossing units on canted track .....</b>   | <b>68</b> |
| <b>F.7 Vertical alignments and switch and crossing units .....</b>   | <b>68</b> |
| <b>Annex G (informative) Examples of applications .....</b>  | <b>71</b> |
| <b>G.1 General .....</b>   | <b>71</b> |
| <b>G.2 Example of crossover on horizontal curve .....</b>  | <b>71</b> |
| <b>G.3 Example of bi-linear cant transition .....</b>  | <b>72</b> |
| <b>G.4 Example where a cant transition is designed without a coinciding transition curve .....</b>               | <b>73</b> |
| <b>G.5 Example of substandard transition curve .....</b>   | <b>74</b> |
| <b>G.6 Example where several alignment elements forms an intermediate length .....</b>                           | <b>75</b> |
| <b>Annex H (informative) Examples of local limits for cant deficiency .....</b>                                  | <b>76</b> |
| <b>Annex I (informative) Considerations regarding cant deficiency and cant excess .....</b>                      | <b>77</b> |
| <b>I.1 Introduction .....</b>  | <b>77</b> |
| <b>I.2 Cant deficiency .....</b>   | <b>77</b> |
| <b>I.3 Cant excess .....</b>   | <b>77</b> |
| <b>I.4 Wheel climb criterion .....</b>   | <b>77</b> |
| <b>I.5 Vehicle overturning .....</b>   | <b>78</b> |
| <b>I.6 The lateral strength of a track under loading (Prud'homme limit) .....</b>                                | <b>78</b> |
| <b>I.7 Cant deficiency at switch and crossing layouts on curves .....</b>  | <b>78</b> |
| <b>Annex J (informative) Passenger comfort on curves .....</b>   | <b>79</b> |
| <b>J.1 General .....</b>   | <b>79</b> |
| <b>J.2 Lateral acceleration .....</b>  | <b>79</b> |
| <b>J.3 Lateral jerk .....</b>  | <b>79</b> |
| <b>J.3.1 Lateral jerk as a function of rate of change of cant deficiency .....</b>                               | <b>79</b> |
| <b>J.3.2 Lateral jerk as a function of an abrupt change of cant deficiency .....</b>                             | <b>80</b> |
| <b>J.4 Roll motions .....</b>  | <b>80</b> |
| <b>Annex K (normative) Sign rules for calculation of D, I and p .....</b>  | <b>81</b> |
| <b>K.1 General regarding the sign rules .....</b>  | <b>81</b> |
| <b>K.2 Sign rules for calculation of D .....</b>   | <b>81</b> |
| <b>K.3 Sign rules for calculation of I .....</b>   | <b>81</b> |
| <b>K.4 Sign rules for calculation of p .....</b>   | <b>82</b> |
| <b>Annex L (informative) Length of constant cant between two linear cant transitions Li .....</b>                | <b>84</b> |
| <b>Annex M (informative) The principle of virtual transition .....</b>   | <b>85</b> |
| <b>M.1 Virtual transition at an abrupt change of cant deficiency .....</b>                                       | <b>85</b> |
| <b>M.2 Virtual transition at a short intermediate length between two abrupt changes of cant deficiency .....</b> | <b>86</b> |
| <b>M.3 Limits based on the principle of the virtual transition .....</b>   | <b>87</b> |

|   |   |           |
|---|---|-----------|
| <b>M.3.1</b>  | <b>General .....</b>  | <b>87</b> |
| <b>M.3.2</b>  | <b>Characteristic vehicle with a distance of 20 m between bogie centres .....</b>   | <b>87</b> |
| <b>M.3.3</b>  | <b>Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres .....</b>                           | <b>87</b> |
| <b>Annex N (normative) Lengths of intermediate elements Lc to prevent buffer locking .....</b>  |   | <b>89</b> |
| <b>N.1</b>  | <b>General .....</b>  | <b>89</b> |
| <b>N.2</b>  | <b>Basic vehicles and running conditions .....</b>  | <b>89</b> |
| <b>N.3</b>  | <b>Lengths Lc of an intermediate straight track between two long circular curves in the<br/>opposite directions .....</b> | <b>89</b> |
| <b>N.4</b>  | <b>General cases for end throw differences .....</b>  | <b>90</b> |
| <b>Annex O (informative) Considerations for track gradients .....</b>   |   | <b>93</b> |
| <b>O.1</b>  | <b>Uphill gradients .....</b>   | <b>93</b> |
| <b>O.2</b>  | <b>Downhill gradients .....</b>   | <b>93</b> |
| <b>O.3</b>  | <b>Gradients for stabling tracks and at platforms .....</b>   | <b>93</b> |
| <b>Annex ZA (informative) Relationship between this European Standard and the Essential<br/>Requirements of EU Directive 2008/57/EC .....</b> |   | <b>94</b> |
| <b>Bibliography .....</b>   |   | <b>97</b> |