

DIN EN 15273-3:2017-10 (E)

Railway applications - Gauges - Part 3: Structure gauges (includes Amendment A1:2016)

Contents		Page
European foreword		9
Introduction		10
1	Scope	11
2	Normative references	12
3	Terms and definitions	12
3.1	structure gauge	12
3.1.1	structure verification limit gauge	12
3.1.2	structure installation limit gauge	12
3.1.3	structure installation nominal gauge	13
3.2	distance between track centres	13
3.2.1	verification limit distance between centres	13
3.2.2	installation limit distance between centres	13
3.2.3	installation nominal distance between centres	14
4	Symbols, abbreviations and subscripts	15
4.1	Symbols and abbreviations	15
4.2	Subscripts	21
4.3	Notations	21
5	General information on all the gauging methods	22
5.1	The reference profile and its associated rules	22
5.2	Transverse widening	22
5.2.1	Gauge variations depending on the local situation	22
5.2.2	Random transverse phenomena	23
5.3	Superelevation and lowering perpendicular to the running surface	24
5.3.1	General	24
5.3.2	Vertical superelevation or lowering for longitudinal profile transition curves	24
5.3.3	Vertical effect of the roll	25
5.3.4	Uplift	27
5.3.5	Vertical random phenomena	27
5.4	Additional allowances	27
5.5	Gauge types	27
5.5.1	Gauge methodologies	27
5.5.2	Structure gauge types	28
5.5.3	Uniform gauge	28
5.6	Choice of gauge	29
5.6.1	Gauge and methodology choice	29
5.6.2	Structure gauge choice	29
5.6.3	Taking account of the allowances	29
5.6.4	Catalogue of gauges	30
6	Rules for determination of the static gauge	30
6.1	General	30
6.2	Associated rules	30
6.3	Transverse clearances	32
6.3.1	Phenomena considered	32
6.3.2	Determination of the sum of allowances j	32

6.4	Vertical allowances for random phenomena	33
6.4.1	Phenomena considered	33
6.4.2	Determination of the sum of vertical allowances V	33
7	Rules for determination of the kinematic gauge	33
7.1	General	33
7.2	Associated rules	34
7.3	Transverse allowances for random phenomena	35
7.3.1	Phenomena considered	35
7.3.2	Determination of the sum of transverse allowances j	35
7.4	Vertical allowances for random phenomena	36
7.4.1	Phenomena considered	36
7.4.2	Determination of the sum of vertical allowances V	36
8	Rules for determination of the dynamic gauge	36
8.1	General	36
8.2	Associated rules	37
8.3	Transverse allowances for random phenomena	37
8.3.1	Phenomena considered	37
8.3.2	Determination of the sum of allowances j	38
8.4	Vertical allowances for random phenomena	38
8.4.1	Phenomena considered	38
8.4.2	Determination of the sum of vertical allowances V	38
9	Distance between track centres	39
9.1	General	39
9.2	Determination of the limit distance between track centres	39
9.2.1	General	39
9.2.2	Effect of cant difference bD	40
9.2.3	Allowances to take into account random phenomena	41
9.2.4	Determination	42
9.3	Determination of the nominal distance between track centres	43
9.3.1	General	43
9.3.2	Determination	43
10	Elements of variable layout	43
10.1	General	43
10.1.1	Calculation principle	43
10.1.2	Characteristics of a layout transition	44
10.1.3	Gauge variations	44
10.2	Layout transition	45
10.2.1	Sudden change of curvature	45
10.2.2	Smooth transition of curvature	46
10.3	Crossing of a switch or crossing	47
10.3.1	General	47
10.3.2	Additional overthrow variations	48
10.3.3	Quasi-static effect variations	49
10.3.4	Result	49
11	Determination of the pantograph free passage gauge	49
11.1	General	49
11.1.1	Space to be cleared for electrified lines	49
11.1.2	Particularities	50
11.1.3	Basic principles	50
11.2	Determination of the pantograph free passage mechanical gauge (in the case of the kinematic gauge)	51
11.2.1	Determination of the mechanical gauge width	51
11.2.2	Determination of the maximum height heff of the mechanical gauge	53
11.3	Pantograph electrical gauge (in the case of the kinematic gauge)	54
11.3.1	General	54
11.3.2	Pantograph electrical gauge width	54
11.3.3	Electrical gauge height	54

11.3.4	Insulating distance	55
11.4	Determination of the pantograph gauge in the case of the dynamic gauge	55
12	Overhead contact wire	55
13	Rules for installation of platform edges	56
13.1	General	56
13.2	Gap h _{lac} 0 and h _{lac} 0	59
13.3	Installation dimensions	61
13.3.1	Installation relative to the running surface	61
13.3.2	Installation relative to the horizontal (x _q , y _q)	61
13.3.3	Installation tolerances	62
13.4	Verification and tolerances	62
14	Tilting trains	62
14.1	General	62
14.2	Transition curve	63
14.3	Degraded modes	64
15	Rules for ferries	64
16	Track accessories	64
16.1	General	64
16.2	Contact ramps	65
16.3	Active check rails	65
16.4	Planking of level crossings	65
16.5	Electric third rail	65
16.6	Rail brakes	65
17	Verification and maintenance of the gauge	66
17.1	Structure gauges	66
17.2	Distance between track centres	66
18	Guide for determination of a new gauge from an existing infrastructure	66
Annex A (normative) Calculation methodology for structure gauge allowances		67
A.1	General	67
A.2	Formulation in the case of the kinematic gauge	67
A.2.1	For the installation nominal gauge	67
A.2.2	For the installation limit gauge	68
A.2.3	For the verification limit gauge	70
A.2.4	For the installation nominal distance between centres	71
A.2.5	For the installation limit distance between centres	71
A.2.6	For the verification limit distance between centres	71
A.2.7	For the pantograph gauge	72
A.3	Formulation in the case of the dynamic gauge	72
A.3.1	General	72
A.3.2	For the installation nominal gauge	72
A.3.3	For the installation limit gauge	73
A.3.4	For the verification limit gauge	74
A.3.5	For the nominal installation distance between centres	75
A.3.6	For the verification limit distance between centres	75
A.3.7	For the pantograph gauge	75
Annex B (informative) Recommended values for calculation of the structure gauge and calculation examples		76
B.1	Recommendations for coefficients	76
B.2	Examples of kinematic calculation	78
B.2.1	Verification limit gauge, installation limit gauge and installation nominal gauge	78
B.2.2	Nominal, installation limit and verification limit distances between centres	80

Annex C (normative) International gauges G1, GA, GB and GC, GI1, GI2 and GI3	81	
C.1	General	81
C.1.1	Application	81
C.1.2	Gauge types	81
C.1.3	Parameters and common rules	81
C.1.4	Calculation of distance between centres	82
C.1.5	Pantograph free passage gauge	82
C.1.6	Gauge parts	82
C.2	Gauge for the upper parts (h > 400 mm)	83
C.2.1	Gauge G1	83
C.2.2	Gauges GA and GB	84
C.2.3	Gauge GC	86
C.3	Lower parts (h 0,400 m)	87
C.3.1	Lower parts of GI2 - generally applicable	87
C.3.2	Lower parts of GI1 - Tracks for rail brake equipment	88
C.3.3	Lower parts for "rolling" roads - GI3	93
C.4	Pantograph free passage gauge	95
Annex D (normative) Gauges for multilateral and national agreements	96	
D.1	General	96
D.2	Kinematic gauges derived from international gauges	96
D.2.1	Gauge G2	96
D.2.2	Gauges GB1 and GB2	98
D.3	Static gauges derived from international gauges	100
D.3.1	Gauge G1	100
D.3.2	Gauge G2	104
D.3.3	Static gauges GA, GB and GC (loading gauges)	105
D.4	National application gauge	108
D.4.1	Belgian gauges BE1, BE2 and BE3	108
D.4.2	French gauges FR-3.3	112
D.4.3	Portuguese gauges PTb, PTb+ and PTc	114
D.4.4	Finnish gauge FIN1	120
D.4.5	Swedish gauges SEa and SEc	123
D.4.6	German gauge DE1	126
D.4.7	German gauge DE2	128
D.4.8	German gauge DE3	129
D.4.9	Czech gauge Z-GCD	131
D.4.10	British gauge	132
D.4.11	Spanish gauges GHE16, GEA16, GEB16, GEC16, GEC14, GEE10 and GED10	133
Annex E (informative) Calculation example for determination of the gauge at a switch or crossing	149	
E.1	General	149
E.2	Methodology	150
E.3	Widening in the curve	150
E.3.1	Widening of the main line	150
E.3.2	Widening in the turnout route	152
E.4	The quasi-static effect	153
E.5	Gauge widening at a switch or crossing	154
Annex F (normative) Determination of reference vehicle characteristics	157	
F.1	General	157
F.2	Methodology	157
F.3	Calculation example	158
F.3.1	General	158
F.3.2	Vehicle no. 1 (on the inside of the curve)	158
F.3.3	Vehicle no. 2 (on the outside of the curve)	158
F.3.4	Vehicle no. 3 (on the inside of the curve)	159

F.3.5	Vehicle no. 4 (on the outside of the curve)	159
F.3.6	Summary	159
F.3.7	International gauge reference vehicles	160
Annex G (normative) Uniform gauge		162
G.1	General	162
G.2	GU1	162
G.2.1	General	162
G.2.2	Determination of the gauge	162
G.2.3	Equivalent kinematic gauge	164
G.3	GU2	164
G.3.1	General	164
G.3.2	Determination of the gauge	165
G.4	GUC	166
G.4.1	General	166
G.4.2	Determination of the gauge	167
Annex H (informative) Gauge maintenance guideline		168
H.1	General	168
H.2	Choice of gauge	168
H.3	Installation rules	168
H.3.1	Guidelines for installation of equipment along the track	168
H.3.2	Guidelines for the installation of tracks alongside structures	168
H.3.3	Guidelines for the installation of temporary structures	169
H.4	Managing and checking of structures	169
H.4.1	Management principles	169
H.4.2	Management of critical situations	169
H.4.3	Practical aspects for measuring the structures	169
H.5	Effect of track maintenance	170
H.6	Personnel training	170
Annex I (informative) A-deviations		171
Annexe ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC		173
Bibliography		177