DIN EN 16729-3:2018-07 (E)

Railway applications - Infrastructure - Non-destructive testing on rails in track - Part 3: Requirements for identifying internal and surface rail defects

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Symbols and abbreviations 9

5 NDT Methods to detect internal and surface rail defects 9
5.1 General 9
5.2 Convention 9
5.3 Visual testing - VT 9
5.3.1 Description 9
5.3.2 Test area 10
5.3.3 Example applications 10
5.4 Automatic visual testing - AVT 10
5.4.1 Description 10
5.4.2 Test area 11
5.4.3 Example applications 11
5.5 Ultrasonic testing - UT 12
5.5.1 Description 12
5.5.2 Test area 12
5.5.3 Example applications 13
5.6 Eddy current testing - ET 13
5.6.1 Description 13
5.6.2 Test area 13
5.6.3 Example applications 14
5.7 Magnetic particle testing - MT 14
5.7.1 Description 14
5.7.2 Test area 15
5.7.3 Example applications 15
5.8 Penetrant testing - PT 15
5.8.1 Description 15
5.8.2 Test area 15
5.8.3 Example applications 15
5.9 Guided Wave Testing - GWT 15
5.9.1 Description 15
5.9.2 Test area 16
5.9.3 Example applications 16

6 NDT detection of internal and surface rail defects 17
6.1 General 17
6.2 Squat 20
6.3 Progressive transverse cracking 22
6.4 Horizontal cracking 24
6.5 Longitudinal vertical cracking (in the head of the rail) 26
6.6 Rail head surface conditions 29

6.7 Head check on the gauge corner 30
6.8 Corrosion 33

Annex ZA (informative) Relationship between this European Standard and the essential requirements of EU Directive 2008/57/EC aimed to be covered 35

Bibliography 37