

DIN CEN/TR 17039:2018-08 (E)

Railway applications - Technical Report about the revision of EN 14363; English
version CEN/TR 17039:2017

Contents		Page
European foreword		5
1	Scope	6
2	Members of the different drafting groups for the revision of EN 14363	6
3	Changes to the scope	7
3.1	Scope extension	7
3.2	Limitation	7
3.3	Clarification	8
3.4	Shifted to other sections	8
4	Fault modes	8
4.1	What was changed?	8
4.2	Why was it changed?	9
4.3	Comments raised in the CRM process and how they were addressed	9
5	Load conditions for testing	9
6	First stage assessment	10
6.1	General	10
6.2	Safety against derailment on twisted track	10
6.3	Safety against derailment under longitudinal compressive forces in S-shaped curves	12
6.4	Evaluation of the torsional coefficient of a car body	12
6.5	Determination of displacement characteristics	12
6.6	Loading of the diverging branch of a switch	13
6.7	Running safety in curved crossings for vehicles with small wheels	14
7	Statistical analysis and multiple regression	14
7.1	Background	14
7.2	Relationship of assessment parameters and input variables	14
7.3	Assessment methods	16
7.4	Assessment by statistical methods in EN 14363	16
7.4.1	General	16
7.4.2	One-dimensional method	16
7.4.3	Two-dimensional method	24
7.4.4	Multiple regression	28
7.5	Regression assumptions	31
8	Recalculation of Y/Q (7.6.2.2.5)	32
8.1	What was changed	32
8.2	Why was it changed	33
8.3	Any references to useful background	33
8.4	What were the options, what was rejected and why?	33
9	Track loading parameters	36
10	Rail surface damage quantity Tqst	36
10.1	What was changed	36
10.2	Why was it changed	36
10.3	Approach	37

10.4	Derivation and definition of Tqst	38
CEN/TR 17039:2017 (E)	10.5 Measurable quantities	39
10.6	Limit values	39
10.7	Verification from tests	40
11	Replacing of limit values of ride characteristics by informative guidance for assessment	40
11.1	General	40
11.2	Removing limit values for quasi-static lateral acceleration	41
11.3	Revision of accelerometer positions in the car body of freight vehicles	42
12	Track geometric quality and coordination with WG 28	42
12.1	Background	42
12.2	Joint Survey Group WG 10 / WG 28	44
12.3	DynoTRAIN project	45
12.4	Use of 50 % and / or 90 % levels	45
12.5	Changes from EN 14363:2005 and UIC 518:2009	45
12.6	Speed range used for Track Quality assessment	46
12.7	Wavelength Ranges	46
12.8	Requirements in different zones	47
12.9	Topics discussed but not changed	47
13	Contact conditions	47
13.1	Equivalent conicity	47
13.1.1	Summary of requirements of EN°14363:2005	47
13.1.2	Summary of requirements of UIC Leaflet 518:2009	48
13.1.3	Changes in EN 14363:2016	48
13.2	Background information about investigations carried out in the DynoTRAIN project	49
13.3	Radial steering index (RSI)	54
13.3.1	Summary of requirements of EN°14363:2005	54
13.3.2	Summary of requirements of UIC Leaflet 518:2009	54
13.3.3	Changes in EN°14363:2016	55
13.3.4	Background information about the radial steering index	55
14	Special vehicles	58
15	Simulation	59
15.1	General	59
15.2	Model validation	60
15.2.1	Principle of model validation	60
15.2.2	Evaluations to carry out model validation	60
15.2.3	Independent review	61
15.2.4	Validation proposal from DynoTRAIN	61
15.2.5	Efficiency of the usage of stationary tests	62
15.3	Fields and conditions for application of simulation	62
15.3.1	Introduction	62
15.3.2	Definitions of reference and modified vehicle	62
15.3.3	Scope of permitted modifications	63
15.3.4	Requirements regarding the modification of a validated model	63
15.3.5	Evaluation of estimated values	64
15.3.6	Application field: Extension of the range of test conditions	64
15.3.7	Application field: Approval of vehicle modification	64
15.3.8	Application field: Approval of new vehicles by comparison with a reference vehicle	65
15.3.9	Application field: Investigation of dynamic behaviour in case of fault modes	65
15.4	Input data for simulation	65
15.4.1	Introduction	65
15.4.2	Track layout	65
CEN/TR 17039:2017 (E)	15.4.3 Track irregularity data	66
15.4.4	Frequency / wavelength content	66
15.4.5	Requirements for variation in input conditions	66

16	Extension of acceptance (Annex U)	66
17	Topics discussed but postponed for future revisions	68
17.1	General	68
17.2	Y/Q	68
17.3	Tqst	68
17.4	Bqst and Bmax	68
17.5	Ya,max	68
17.6	Introduction of high frequency contents to the Q-force limits	68
17.7	Track geometry	69
17.8	Compatibility with track conditions outside the test conditions	69
17.9	WHEEL RAIL Geometric contact conditions	69
17.10	Cyclic top	70
17.11	Over-speed and over Cant deficiency testing	70
17.12	General points	70
18	Influence of the revision of EN 14363 on current TSIs	71
18.1	General	71
18.2	Letter to ERA	71
18.3	Annex 1 to letter to ERA	71
Annex A (informative) Guideline for presentation of results from multiple regression		76
A.1	Introduction and purpose	76
A.2	Principles	76
A.3	Example	77
Bibliography		80