# ISO 20138-1:2018 (E)

## Railway applications — Calculation of braking performance (stopping, slowing and stationary braking) — Part 1: General algorithms utilizing mean value calculation

## Contents


Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Stopping and slowing distances calculation

5.1 General
5.2 Vehicle characteristics
5.2.1 Static mass, mst
5.2.2 Equivalent rotating mass, mrot
5.2.3 Dynamic mass, mdyn
5.2.4 Wheel diameter
5.3 Adhesion wheel/rail dependent brake equipment type characteristics
5.3.1 Basic brake cylinder
5.3.2 Tread brake
5.3.3 Tread brake unit
5.3.4 Disc brake
5.3.5 Electro-dynamic brake
5.3.6 Fluid retarder
5.3.7 Transmission retarder
5.3.8 Rotating eddy current brake
5.4 Adhesion independent brake equipment type characteristics
5.4.1 Magnetic track brake
5.4.2 Linear eddy current brake
5.4.3 Mean retarding force by train resistance
5.4.4 Aerodynamic brake
5.4.5 Electro dynamic brake generated by linear induction motor
5.5 Time characteristics
5.5.1 Derivation of brake equipment time characteristics
5.5.2 Equivalent response time, te
5.6 Initial and operating characteristics
5.6.1 Forces on the slope
5.6.2 Downhill force due to gravity depending on the gradient
5.6.3 Blending
5.6.4 Value of the mean adhesion required between wheel/rail for the braked wheelset
5.7 Stopping and slowing distance calculation based on mean values
5.7.1 Mean retarding force with respect to the distance
5.7.2 Equivalent deceleration, ae, based on retarding forces
5.7.3 Equivalent free running distance, s0
5.7.4 Stopping and slowing distance on level track
5.7.5 Stopping and slowing distance based on different gradients
5.7.5.1 Stopping and slowing distance on a gradient
5.7.5.2 Stopping and slowing distance on a gradient (simplified)
5.8 Supplementary dynamic calculations
5.8.1 General

5.8.2 Braking energy
5.8.2.1 Total energy, Wtot
5.8.2.2 Energy dissipated by each brake equipment type, WB,n
5.8.3 Maximum braking power of each brake equipment type, Pmax,n

6 Stationary braking

6.1 General
6.2 Holding brake
6.3 Immobilization brake
6.4 Parking brake
6.5 Stationary brake calculation
6.5.1 General
6.5.2 General characteristics
6.6 Static coefficient of friction
6.7 Parking brake force provided by equipment type
6.7.1 Screw applied parking brake (tread brake)
6.7.2 Spring applied tread brake unit
6.7.3 Screw applied parking brake (disc brake)
6.7.4 Spring applied disc brake unit arrangement
6.7.5 Force of a permanent magnetic track brake
6.8 Stationary brake force for each wheelset
6.9 Total stationary brake force per train
6.10 Stationary brake safety calculation
6.11 Safety ratio for stationary brake
6.12 Coefficient of adhesion required by each disc braked wheelset
6.13 Maximum achievable gradient
6.14 Method for safety calculation for vehicles with a different relationship between brake force and load per wheelset
6.14.1 General
6.14.2 Mean adhesion value between wheel/rail
6.14.3 Safety against rolling
6.14.4 Safety against sliding
6.14.4.1 General consideration
6.14.4.2 General process
6.14.5 Retention force
6.14.6 Retention Safety

Annex A (informative) Methodology of stopping and slowing distance calculation

Annex B (informative) Workflow for stationary brake calculations

B.1 General
B.2 Methodology for stationary brake calculation
B.3 Workflow for the retention calculation

Annex C (informative) Examples for brake calculation

C.1 Freight wagon with two bogies/four wheelsets/central brake rigging with one brake cylinder and 16 brake blocks
C.1.1 General
C.1.2 Example for brake calculation of a freight wagon
C.2 Coach with two bogies/four wheelsets
C.2.1 General
C.2.2 Example for brake calculation of a coach
C.3 Locomotive (diesel hydraulic engine) with four mechanical coupled wheelsets
C.3.1 General
C.3.2 Example for brake calculation of a Locomotive
C.4 Multiple unit

Annex D (informative) Calculation of braking forces (non-stationary)

D.1 Braking force of magnetic track brake
D.2 Braking force of linear eddy current brake
D.3 Braking force of electro-dynamic brake
D.4 Mean retarding force of fluid retarder