ISO 20138-2:2019-11 (E)

Railway applications - Calculation of bra king performance (stopping, slowing and stationary braking) - Part 2: General al gorithms utilizing step by step calculation

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols 2

5 General explanation of step-by-step calculation 3
5.1 Method 3
5.2 Retarding force models 3
5.3 Algorithm 4
5.3.1 General description 4
5.3.2 Time integration 4
5.3.3 Determination of time step/relative distance deviation 6
5.3.4 Equivalent system response time te 6
5.4 Supplementary dynamic calculations 7
5.4.1 Energy dissipated by each brake equipment type 7
5.4.2 Value of the instantaneous adhesion required between wheel and rail for the braked wheelset (ax) 7
5.4.3 Maximum braking power of each brake equipment type 8

6 Considerations for stopping/slowing distances and deceleration calculations 8
6.1 Accuracy of input values 8
6.2 Distance calculations 8
6.3 General characteristics 8
6.4 Brake equipment type characteristics 9
6.4.1 General 9
6.4.2 Input data 9
6.5 Initial and operating characteristics 9
6.5.1 Nominal conditions 9
6.5.2 Wheel diameter 9
6.5.3 Initial speed 9
6.5.4 Gradient 9
6.5.5 Level of the brake demand 9
6.5.6 Degraded mode 9
6.5.7 Degraded condition 10
6.5.8 Available coefficient of wheel and rail adhesion 10
6.6 Other deceleration calculations 10
6.6.1 General 10
6.6.2 Decelerations resulting from the force generated by each brake equipment type (aj,n) 10
6.6.3 Equivalent (mean) deceleration (ae) based on distance 10

7 Immobilization brake calculation 11

Annex A (normative)Workflowofkineticcalculations 12

Annex B (informative) Calculation of retarding forces (non-stationary) 13

Annex C (informative) Examples for brake calculation 18

Bibliography 33