

DIN EN 13715:2020-10 (E)

Railway applications - Wheelsets and bogies - Wheels - Tread profile

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	General	6
5	Definition of the tread profile	6
6	Symbols and abbreviations	7
7	Construction method	9
7.1	Definition of the axes	9
7.2	Base profile	9
7.3	Profile construction	9
8	Geometric characteristics	14
8.1	R20,5 connecting radius	14
8.2	RE and RI 12 mm connecting radii	14
8.3	Rfa connecting radius	14
8.4	R13 connecting radius	14
8.5	Wheel tread	14
8.6	Reverse slope - Chamfer	14
9	Profile designation	14
10	Verification of the wheel profile	15
Annex A(normative) Flange		16
A.1	Definition of the flange	16
A.2	Flange geometry	17
Annex B(normative) 1/40th profile		18
B.1	Complete reference profile: construction with a 32,5 mm thick flange and 15 % reverse slope	18
B.2	Profile construction: specific zones	18
Annex C(normative) S1002 profile		20
C.1	Complete reference profile: construction with 32,5 mm thick flange and 6,7 % reverse slope	20
C.2	Profile construction: specific zones	20
Annex D(normative) EPS profile		25

D.1	Complete reference profile: construction with 32,5 mm thick flange and 10 % reverse slope	25
D.2	Profile construction: specific zones	25
Annex ZA(informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2016/797/EU aimed to be covered		28
Bibliography		31