DIN EN 13848-6:2021-03 (E)

Railway applications - Track - Track geometry quality - Part 6: Characterisation of track geometry quality (includes Amendment A1:2020)

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviations 5
3.1 Terms and definitions 5
3.2 Symbols and abbreviations 6

4 Basic principles 7
4.1 Introduction 7
4.2 Basic parameters for track geometry quality assessment 7
4.3 Transparency 7
4.4 Complexity 7
4.5 Track-vehicle interaction 7

5 Assessment of track geometry quality: state-of-the-art 7
5.1 General 7
5.2 Standard deviation (SD) 7
5.3 Isolated defects 8
5.4 Combination of various parameters 9
5.4.1 Combined standard deviation (CoSD) 9
5.4.2 Standard deviation of the combinations of parameters 9
5.4.3 Point mass acceleration method (PMA) 10
5.5 Methods based on vehicle response 11
5.5.1 Use of theoretical model 11
5.5.2 Use of direct measurement 11
5.6 Power Spectral Density (PSD) 11

6 Levels of aggregation and calculation methods 12

7 Classes of track geometry quality 13
7.1 General 13
7.2 Description of track quality classes (TQC) 13
7.3 Values of track quality classes 15
7.4 Assignment of TQCs 16
7.5 Possible application of TQCs 16

Annex A(informative) Point mass acceleration method (PMA) 18

A.1 Introduction 18
A.2 Description of the PMA model 18
A.3 Calculation of the PMA-assessment figure 18
A.4 Features of the PMA method 19

Annex B(informative) Vehicle Response Analysis methods (VRA) 21

B.1 Introduction 21
B.2 Determination of the assessment functions 21
B.3 Application of the assessment functions 23

B.4 Features of VRA methods 25

Annex C(normative) Method for calculating reference TQIs (TQIref) 26

C.1 Introduction 26
C.2 Description of the reference method 26

Annex D(informative) Method of classification of alternative TQI using the TQCs 28

D.1 Introduction 28
D.2 Description of the conversion method 28

Bibliography 30