ISO 19659-2:2020 (E)

Railway applications — Heating, ventilation and air conditioning systems for rolling stock — Part 2: Thermal comfort

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Category of passenger railway vehicles

- 4.1 General
- 4.2 Category 1 (e.g. main line, intercity, long-distance, high speed)
- 4.3 Category 2 (e.g. suburban, commuter, regional)
- 4.4 Category 3 (e.g. urban, LRV, tram, metro/subway)

5 Design conditions

- 5.1 General
- 5.2 Exterior design conditions
- 5.2.1 Parameters
- 5.2.2 Temperature and corresponding relative humidity
- 5.2.3 Solar radiation
- 5.2.4 Altitude
- 5.2.5 Train speed
- 5.3 Extreme exterior conditions
- 5.4 Interior design conditions
- 5.4.1 Internal heat gains
- 5.4.2 Temperature and corresponding relative humidity

6 Interior temperature setting (Tic)

7 Thermal comfort parameters

- 7.1 General
- 7.2 Interior air temperature in the comfort zone
- 7.2.1 Mean interior temperature range (difference between Tim and Tic)
- 7.2.2 Horizontal temperature range (ΔTh)
- 7.2.3 Vertical temperature range (ΔTv)
- 7.3 Relative humidity in the comfort zone
- 7.4 Surface temperature on the comfort envelope
- 7.5 Air velocity in the comfort zone
- 7.6 Interior temperature in the local annexes
- 7.7 Air quality
- 7.7.1 Fresh air volume flow rate into the comfort zone
- 7.7.2 Particulate filtration of the air
- 7.7.3 Air transfer between interior zones

8 Air movement tests

- 8.1 General
- 8.2 Air volume flow rate
- 8.3 Air velocity
- 8.4 Air transfer between interior zones

9 Climatic tests

9.1 General
9.2 Type of tests
9.2.1 General
9.2.2 Design conditions test
9.2.3 Extreme conditions test
9.2.4 Regulation test
9.2.5 Door open/close cycling test
9.3 Test programme

10 Characteristics of the test facility and equipment

10.1 General
10.2 Exterior temperature
10.3 Relative humidity
10.4 Occupation
10.5 Wind speed (if required)
10.6 Equivalent solar load

11 Recording and measuring instruments

11.1 General
11.2 Recording
11.3 Temperature
11.4 Relative humidity
11.5 Air velocity
11.6 Air volume flow rate
11.7 Wind speed (if required)
11.8 Equivalent solar load (if required)
11.9 Energy consumption and power rating

12 Position of measuring points

12.1 General
12.2 Position of sensors in the passenger railway vehicle
12.2.1 General
12.2.2 Interior air temperature
12.2.3 Relative humidity
12.2.4 Surface temperature
12.2.5 Air velocity
12.2.6 Interior temperature in the local annex
12.3 Position of sensors in the test facility
12.3.1 General
12.3.2 Exterior air temperature
12.3.3 Relative humidity
12.3.4 Wind speed (if required)
12.3.5 Equivalent solar load (if required)
12.4 Position of sensors for testing where no test facility exists
12.4.1 General
12.4.2 Exterior air temperature
12.4.3 Relative humidity
12.4.4 Wind speed
12.4.5 Solar load (if required)

Annex A (informative) Example of exterior design temperature and corresponding relative humidity

A.1 General
A.2 Japanese standard: JIS E 6603
A.3 Chinese standards: GB/T 33193.1
A.4 European standards: EN 13129, EN 14750
A.5 ASHRAE Guideline 23-2016
A.5.1 Cooling
A.5.2 Heating

Annex B (informative) PMV calculation results per each vehicle category

B.1 General
B.2 PMV calculation hypothesis
B.3 PMV calculation results

Annex C (informative) Method to calculate the recommended air velocity range

Page count: 31