

# DIN EN 13232-4:2023-12 (E)

## Railway applications - Track - Switches and crossings for Vignole rails - Part 4: Actuation, locking and detection

---

| <b>Contents</b>  |   | <b>Page</b> |
|--|---|-------------|
| European foreword .....  |   | 3           |
| <b>1</b>   | <b>Scope .....</b>  | <b>5</b>    |
| <b>2</b>   | <b>Normative references .....</b>   | <b>5</b>    |
| <b>3</b>   | <b>Terms and definitions .....</b>  | <b>6</b>    |
| <b>3.1</b>   | <b>General .....</b>  | <b>6</b>    |
| <b>3.2</b>   | <b>Actuation forces .....</b>   | <b>7</b>    |
| <b>3.3</b>   | <b>Geometrical parameters .....</b>   | <b>8</b>    |
| <b>3.4</b>   | <b>Movement and retention of switches and crossings with moveable parts .....</b> | <b>12</b>   |
| <b>3.5</b>   | <b>Movement of switch rails .....</b>   | <b>13</b>   |
| <b>3.6</b>   | <b>Dynamics of the wheel .....</b>  | <b>14</b>   |
| <b>4</b>   | <b>Design criteria .....</b>  | <b>15</b>   |
| <b>4.1</b>   | <b>Parameters required .....</b>  | <b>15</b>   |
| <b>4.2</b>   | <b>Calculations and verifications .....</b>                                       | <b>15</b>   |
| <b>4.2.1</b>   | <b>Object detection between stock rail and switch rail .....</b>                  | <b>15</b>   |
| <b>4.2.2</b>   | <b>Calculation of minimum flangeway .....</b>                                     | <b>16</b>   |
| <b>4.2.3</b>   | <b>Correct closing .....</b>  | <b>17</b>   |
| <b>4.2.4</b>   | <b>Neutral position .....</b>   | <b>17</b>   |
| <b>4.2.5</b>   | <b>Negative force .....</b>   | <b>17</b>   |
| <b>4.2.6</b>   | <b>Mechanical integrity .....</b>   | <b>17</b>   |
| <b>5</b>   | <b>Test methods .....</b>   | <b>17</b>   |
| <b>5.1</b>   | <b>Obstacle detection .....</b>   | <b>17</b>   |
| <b>5.2</b>   | <b>Minimum flangeway / free passage of wheel .....</b>                            | <b>17</b>   |
| <b>5.3</b>   | <b>Correct closing .....</b>  | <b>18</b>   |
| <b>5.4</b>   | <b>Actuation force, <math>F_a</math> .....</b>                                    | <b>18</b>   |
| <b>5.5</b>   | <b>Neutral position .....</b>   | <b>18</b>   |
| <b>5.6</b>   | <b>Negative force .....</b>   | <b>18</b>   |
| <b>5.7</b>   | <b>Trailability .....</b>   | <b>19</b>   |
| <b>5.7.1</b>   | <b>General .....</b>  | <b>19</b>   |
| <b>5.7.2</b>   | <b>Factory testing .....</b>  | <b>19</b>   |
| <b>5.7.3</b>   | <b>Track testing .....</b>  | <b>19</b>   |
| <b>6</b>   | <b>Acceptance .....</b>   | <b>19</b>   |
| <b>6.1</b>   | <b>General .....</b>  | <b>19</b>   |
| <b>6.2</b>   | <b>Standard testing (no prototypes) .....</b>                                     | <b>19</b>   |
| <b>6.3</b>   | <b>Prototype testing .....</b>  | <b>20</b>   |
| <b>6.4</b>   | <b>Testing requirements for change in flexibility .....</b>                       | <b>20</b>   |
| <b>Annex A (informative) Commonly used values for obstacle detection .....</b>   |   | <b>21</b>   |
| <b>Annex B (informative) Commonly used values for flangeway .....</b>  |   | <b>22</b>   |
| <b>Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive (EU) 2016/797 aimed to be covered .....</b> |   | <b>23</b>   |
| <b>Bibliography .....</b>  |   | <b>25</b>   |