

DIN EN 16186-8:2022-06 (E)

Railway applications - Driver's cab - Part 8: Tram vehicle layout and access

| Contents | | Page |
|-------------------------|--|-------------|
| European Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols and abbreviations | 7 |
| 5 | Access, egress and doors | 7 |
| 5.1 | General | 7 |
| 5.1.1 | External steps and handrails | 7 |
| 5.1.2 | Access and security | 7 |
| 5.1.3 | Door handles | 8 |
| 5.1.4 | Threshold | 8 |
| 5.1.5 | Ergonomics | 8 |
| 5.1.6 | External doors | 8 |
| 5.1.7 | Internal doors giving access to the driver's cab | 9 |
| 6 | Floor and flooring | 10 |
| 6.1 | Floor surface criteria | 10 |
| 6.2 | Steps | 10 |
| 7 | Windows and glazing | 11 |
| 7.1 | Mechanical characteristics of glass | 11 |
| 7.2 | Operation of opening windows | 11 |
| 8 | Emergency | 11 |
| 8.1 | Driver's cab emergency exits | 11 |
| 8.1.1 | General | 11 |
| 8.1.2 | Minimum escape route | 11 |
| 8.1.3 | Emergency exit opening | 11 |
| 8.2 | Emergency egress from seat | 12 |
| 8.2.1 | Seat design for escape | 12 |
| 8.2.2 | Escape from seat assessment criteria | 12 |
| 9 | Layout | 12 |
| 9.1 | General | 12 |
| 9.2 | Prevention of occupational injuries | 13 |
| 9.2.1 | General | 13 |
| 9.2.2 | Exposed edges | 13 |
| 9.3 | Comfort angles | 14 |
| 9.4 | Interior space | 16 |
| 9.5 | Driver's desk | 16 |
| 9.6 | Footrest | 16 |
| 9.7 | Storage space | 17 |
| 9.7.1 | General | 17 |
| 9.7.2 | Storage of personal belongings | 17 |
| 9.7.3 | Emergency equipment | 17 |
| 9.8 | Seats | 17 |
| 9.8.1 | General | 17 |

| | | |
|---|--|-----------|
| 9.8.2 | Driver's seat | 17 |
| 9.8.3 | Additional seats | 19 |
| 9.9 | Surface finish | 19 |
| 9.10 | Privacy shield | 19 |
| 10 | Lighting | 20 |
| 11 | Marking and labelling in driver's cab | 20 |
| Annex A (normative) Driver's seat dimensions and driver's seat integration | | 21 |
| Annex B (normative) Minimum leg clearance | | 25 |
| Annex C (normative) Mandatory labels | | 26 |
| Bibliography | | 27 |