DIN EN 16186-8:2022-06 (E)

Railway applications - Driver's cab - Part 8: Tram vehicle layout and access

Contents

Page

European Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Symbols and abbreviations 7

5 Access, egress and doors 7
5.1 General 7
5.1.1 External steps and handrails 7
5.1.2 Access and security 7
5.1.3 Door handles 8
5.1.4 Threshold 8
5.1.5 Ergonomics 8
5.1.6 External doors 8
5.1.7 Internal doors giving access to the driver's cab 9

6 Floor and flooring 10
6.1 Floor surface criteria 10
6.2 Steps 10

7 Windows and glazing 11
7.1 Mechanical characteristics of glass 11
7.2 Operation of opening windows 11

8 Emergency 11
8.1 Driver's cab emergency exits 11
8.1.1 General 11
8.1.2 Minimum escape route 11
8.1.3 Emergency exit opening 11
8.2 Emergency egress from seat 12
8.2.1 Seat design for escape 12
8.2.2 Escape from seat assessment criteria 12

9 Layout 12
9.1 General 12
9.2 Prevention of occupational injuries 13
9.2.1 General 13
9.2.2 Exposed edges 13
9.3 Comfort angles 14
9.4 Interior space 16
9.5 Driver's desk 16
9.6 Footrest 16
9.7 Storage space 17
9.7.1 General 17
9.7.2 Storage of personal belongings 17
9.7.3 Emergency equipment 17
9.8 Seats 17
9.8.1 General 17

9.8.2 Driver's seat 17
9.8.3 Additional seats 19
9.9 Surface finish 19
9.10 Privacy shield 19

10 Lighting 20

11 Marking and labelling in driver's cab 20

Annex A (normative) Driver's seat dimensions and driver's seat integration 21

Annex B (normative) Minimum leg clearance 25

Annex C (normative) Mandatory labels 26

Bibliography 27