

DIN EN 17636:2023-12 (E)

Railway applications - Infrastructure - Track alignment design parameters - Urban rail

Contents		Page
European foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and abbreviations	9
5	General	10
5.1	Background	10
5.2	Line categories	10
5.3	Alignment characteristics	11
6	Limits for 1 435 mm and 1 000 mm nominal track gauge	13
6.1	Horizontal radius R	13
6.2	Applied cant D	13
6.3	Cant deficiency I	14
6.4	Cant excess E	15
6.5	Length of cant transition DL and/or transition curve in the horizontal plane LK	15
6.5.1	General	15
6.5.2	Length of linear cant transition and/or clothoid	16
6.6	Cant gradient d / dD s	16
6.7	Rate of change of cant d / dD t	17
6.8	Rate of change of cant deficiency d / dl t	17
6.9	Length of constant cant between two linear cant transitions Li	18
6.10	Abrupt change of horizontal curvature	18
6.11	Abrupt change of cant deficiency I	18
6.12	Length between two abrupt changes of horizontal curvature Lc	19
6.13	Length between two abrupt changes of cant deficiency Ls	20
6.14	Track gradient p	20
6.15	Length of constant track gradient Lg	21
6.16	Vertical radius Rv	21
6.17	Length of vertical curve Lv	23
6.18	Abrupt change of track gradient p	23
Annex A (normative) Rules for converting parameter values for nominal track gauges other than 1 435 mm		24
A.1	General	24
A.2	Symbols and abbreviations	24
A.3	Basic assumptions and equivalence rules	26
A.3.1	General	26
A.3.2	Basic formulae	26
A.3.3	Basic data	27
A.4	Detailed conversion rules	27
A.4.1	General	27
A.4.2	Cant D1 (6.2)	27
A.4.3	Cant deficiency I1 (6.3)	29
A.4.4	Cant excess E1 (6.4)	30

A.4.5	Length of cant transition LD and transition curve in the horizontal plane LK (6.5)	31
A.4.6	Cant gradient dD/dt (6.6)	31
A.4.7	Rate of change of cant $1d / dD t$ (6.7)	32
A.4.8	Rate of change of cant deficiency dI/dt (6.8)	33
A.4.9	Abrupt change of curvature and abrupt change of cant deficiency I1 (6.10 and 6.11)	34
A.4.10	Other parameters (6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16, 6.17 and 6.18)	34
Annex B (normative) Three-dimensional track geometry with regards to resulting cant gradient and resulting vertical radius		
B.1	General considerations regarding three-dimensional track geometry	35
B.2	Angular twist TA and resulting cant gradient $(dD/ds)_r$	35
B.2.1	Calculation of resulting cant gradient $(dD/ds)_r$ where cant is applied by lifting one rail / 2D and lowering the other rail / 2D	35
B.2.2	Calculation of resulting cant gradient $(dD/ds)_r$ when cant is applied by lifting one rail D	36
B.3	Resulting vertical radius $(R_v)_r$	36
Annex C (informative) The relations between cant deficiency, non-compensated lateral acceleration and related parameters		
C.1	Introduction	38
C.2	Applied cant and roll angle	38
C.3	Equilibrium cant	39
C.4	Cant deficiency and non-compensated lateral acceleration	40
C.5	Applications	41
Annex D (normative) Sign rules for calculation of D , I and p		
D.1	General regarding the sign rules	42
D.2	Sign rules for calculation of D	42
D.3	Sign rules for calculation of I	42
D.4	Sign rules for calculation of p	43
Annex E (normative) Lengths of intermediate elements Lc between small radius curves in opposite directions		
E.1	General	45
E.2	Lengths of intermediate elements Lc for Line Category A1435	45
E.3	Lengths of intermediate elements Lc for Line Category B1435 and C1000	46
Bibliography		48