

# DIN EN 15355:2024-08 (E)

## Railway applications - Braking - Distributor valves and distributor-isolating devices (includes Amendment :2023)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>14</b>
<b>4.1</b>	<b>Symbols .....</b>	<b>14</b>
<b>4.2</b>	<b>Abbreviations .....</b>	<b>14</b>
<b>5</b>	<b>Requirements to function, design and manufacturing .....</b>	<b>14</b>
<b>5.1</b>	<b>Functional requirements .....</b>	<b>14</b>
<b>5.2</b>	<b>Control chamber .....</b>	<b>14</b>
<b>5.3</b>	<b>Pilot volume .....</b>	<b>14</b>
<b>5.4</b>	<b>Auxiliary reservoir volume and brake cylinder size .....</b>	<b>14</b>
<b>5.5</b>	<b>Shock and vibration .....</b>	<b>15</b>
<b>5.6</b>	<b>Service life .....</b>	<b>15</b>
<b>5.7</b>	<b>Compressed air quality .....</b>	<b>15</b>
<b>5.8</b>	<b>Environmental conditions .....</b>	<b>15</b>
<b>5.8.1</b>	<b>General .....</b>	<b>15</b>
<b>5.8.2</b>	<b>Ambient temperature .....</b>	<b>15</b>
<b>5.8.3</b>	<b>Altitude .....</b>	<b>15</b>
<b>5.8.4</b>	<b>Humidity .....</b>	<b>15</b>
<b>5.8.5</b>	<b>Other environmental specifications .....</b>	<b>16</b>
<b>5.9</b>	<b>Design requirements regarding structural integrity at maximum pressure .....</b>	<b>17</b>
<b>5.10</b>	<b>Tightness .....</b>	<b>17</b>
<b>5.11</b>	<b>Fire behaviour .....</b>	<b>17</b>
<b>6</b>	<b>Functional requirements and Type tests .....</b>	<b>17</b>
<b>6.1</b>	<b>General .....</b>	<b>17</b>
<b>6.2</b>	<b>Test benches .....</b>	<b>17</b>
<b>6.3</b>	<b>Functional requirements and tests .....</b>	<b>18</b>
<b>6.3.1</b>	<b>General .....</b>	<b>18</b>
<b>6.3.2</b>	<b>Tightness .....</b>	<b>18</b>
<b>6.3.3</b>	<b>Inexhaustibility .....</b>	<b>20</b>
<b>6.3.4</b>	<b>Compensation of output pressure during brake application .....</b>	<b>24</b>
<b>6.3.5</b>	<b>Normal working pressure .....</b>	<b>25</b>
<b>6.3.6</b>	<b>Released and stand by position .....</b>	<b>26</b>
<b>6.3.7</b>	<b>Maximum output pressure in relation to input pressure reduction .....</b>	<b>29</b>
<b>6.3.8</b>	<b>Maximum output pressure and build-up and release times of an individual distributor valve .....</b>	<b>30</b>
<b>6.3.9</b>	<b>Release time within a train consist .....</b>	<b>31</b>
<b>6.3.10</b>	<b>Sensitivity .....</b>	<b>32</b>
<b>6.3.11</b>	<b>Insensitivity .....</b>	<b>33</b>
<b>6.3.12</b>	<b>Control sensitivity and hysteresis .....</b>	<b>34</b>
<b>6.3.13</b>	<b>Quick service function .....</b>	<b>35</b>
<b>6.3.14</b>	<b>Propagation speed .....</b>	<b>36</b>
<b>6.3.15</b>	<b>Inshot function .....</b>	<b>37</b>
<b>6.3.16</b>	<b>Manual release function .....</b>	<b>38</b>

6.3.17	Distributor isolating device .....	41
6.3.18	Protection against input pressure overcharge .....	46
6.3.19	Initial charging of the brake system of a vehicle .....	49
6.3.20	Initial charging of the brake system of a train .....	50
6.3.21	Maximum supply pressure .....	51
6.3.22	Tests at different temperatures .....	51
6.3.23	Shock and vibration .....	53
6.3.24	Distributor dump valve .....	54
7	In-service assessment .....	55
8	Designation .....	55
9	Identification and marking .....	55
9.1	Distributor valve .....	55
9.2	Distributor-isolating device .....	56
Annex A (normative) Test benches .....		57
A.1	General .....	57
A.2	Test bench Type A for single vehicle .....	57
A.3	Test bench Type B for train with 400 m length .....	59
A.4	Test bench Type C for train with 500 m length .....	59
A.5	Test bench Type D for train with 750 m length .....	59
A.6	Test bench Type E for train with 1 200 m length .....	59
Annex B (normative) Handle for operating the distributor-isolating device .....		60
Annex C (normative) In-service assessment .....		61
Annex D (normative) Handles for the activation of manual release functions .....		62
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive (EU) 2016/797 aimed to be covered .....		64
Bibliography .....		66