

DIN EN 16186-6:2024-12 (E)

Railway applications - Driver's cab - Part 6: Integration of displays, controls and indicators for tram vehicles

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Symbols and abbreviations	9
5	Displays, controls and warnings for operational functions	9
5.1	General	9
5.2	Displays for communication, monitoring and control	9
5.3	Controls	10
5.3.1	Driver's master controller	10
5.3.2	Control for driver activity	10
5.3.3	Control for running direction selection	10
5.3.4	Controls for external lights	10
5.3.5	Controls for Intercom	10
5.3.6	Controls for passenger doors	11
5.3.7	Controls for obstacle detection and pedestrian protection	11
5.3.8	Controls for driver's cab temperature	11
5.3.9	Controls for passenger area temperature	11
5.3.10	Controls for coupled vehicles	11
5.3.11	Distress button	12
5.3.12	Other controls	12
5.3.13	Controls for auxiliary desk	12
5.4	Alarms	13
5.4.1	General	13
5.4.2	Alarm due to a safety system	13
5.4.3	Alarm due to brake failure	13
5.4.4	Alarm due to emergency opening of one or more external doors	13
5.4.5	Driver interface with fire extinguishing system	13
6	Characteristics of displays, controls and indicators	14
6.1	General	14
6.1.1	Design principles	14
6.1.2	Resistance to damage from cleaning agents	14
6.1.3	Labelling	14
6.2	Characteristics of controls	14
6.2.1	General principles	14
6.2.2	Design criteria	15
6.2.3	Characteristics of specific controls	15
6.3	Characteristics of indicators - readability	16
6.4	Characteristic of warnings	16
6.4.1	General	16
6.4.2	Hierarchy of audible warnings	16
6.4.3	Audibility of driving related acoustic signals	16
6.5	Characteristic of loudspeakers	16

7	Positioning of displays and controls	16
7.1	General rules for arrangements	16
7.1.1	Driver's desk design	16
7.1.2	Human factors/ergonomic aspects	17
7.1.3	Device positioning principle	17
7.2	Positioning of displays	18
7.2.1	Display location and orientation	18
7.2.2	Preferred fields of view	18
7.2.3	Positioning speed and ATP signalling information	18
7.2.4	Positioning of other equipment	18
7.3	Positioning of controls	18
7.3.1	Reachability of controls on the driver's desk of tram vehicles	18
7.3.2	Reachability of controls on the driver's desk of tram-train vehicles	19
7.3.3	Grouping of controls	19
7.3.4	Allocation to hands	20
7.3.5	Accessibility	20
7.3.6	Synchronous operation of elements	20
7.3.7	Risk of inadvertent activation	20
7.3.8	Position of specific controls	20
7.3.9	Controls used while driving, but not located on the driver's desk	21
7.3.10	Controls only operated during standstill	21
8	Lighting of cab, displays, controls and indicators	22
8.1	Cab lighting	22
8.2	Instruments' lighting	22
8.3	Prevent disturbing the driver	22
8.4	Reading zone of tram-train vehicles	22
9	Symbol and text definition	22
9.1	Symbol appearance	22
9.2	Harmonized symbols	22
9.2.1	General	22
9.2.2	Combinations of colours	23
9.2.3	Style of symbols	23
9.2.4	Location with respect to controls	23
9.2.5	Field for symbols	23
9.2.6	New symbols	23
9.3	Character type	23
Annex A (normative) Reach envelopes and fields of view inside the cab		24
Annex B (informative) Operating elements and integration at the driver's desk		26
Bibliography		41