

DIN EN 15313:2024-12 (E)

Railway applications - In-service wheelset operation requirements - In-service and off-vehicle wheelset maintenance

Contents		Page
European foreword		6
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms, definitions, symbols and abbreviated terms	9
4	Maintenance	11
4.1	General	11
4.2	Maintenance organization	11
4.2.1	Maintenance organization plan	11
4.2.2	Maintenance plan	11
4.2.3	Service experience	12
4.2.4	Traceability - storage - transportation	12
4.3	Equipment and systems	14
4.4	Staff certification and competence	14
4.5	Qualification of an undertaking for the maintenance of in-service or off-vehicle wheelsets	14
5	Definition and illustrations of a wheelset, its associated components and defects	15
5.1	Definition and illustrations of a wheelset	15
5.1.1	Wheelset	15
5.1.2	Axle	17
5.1.3	Wheel	18
5.1.4	Axlebox	19
5.2	Functional references of the rail-wheel interface	20
5.2.1	Wheelset functional references	20
5.2.2	Wheel functional references	21
5.3	Definitions and illustrations of defects	21
6	Requirements and operations	22
6.1	General	22
6.2	Requirements	22
6.2.1	In-service limit dimensions and positions	22
6.2.2	Special maintenance action for freight wagon axles according to axle load	26
6.2.3	Maintenance decision criteria for in-service wheels for all types of wheel	27
6.2.4	Maintenance decision criteria for in-service wheels for specific wheel types	30
6.2.5	Damage acceptance limits for axle bodies	31
6.2.6	Criteria for axlebox (C.5)	32
6.2.7	Criteria on wheelsets	32
6.2.8	Specific requirements for tyred wheels and resilient wheels	33
6.2.9	Limit value for axle wheel seat diameter	34
6.3	Reprofiling operation	34
6.4	Dimensions after reprofiling	35
6.4.1	Front-to-front dimension "a2"	35
6.4.2	Diameter difference between wheels on the same axle	35
6.4.3	Limit values of radial run-out as a function of the maximum operating speed authorized for the vehicle	35

6.4.4	Wheel axial run-out as a function of the maximum operating speed authorized for the vehicle	35
6.4.5	Parts of the tread that are not re-profiled	35
6.4.6	Radial marks and radial defects on the internal side of the rim	36
6.5	Maintenance operations, examinations and inspections	36
6.5.1	General	36
6.5.2	Detection of tread defects	36
6.5.3	Detection of thermal damage on the wheel rim or tyre	36
6.5.4	Detection of wheel tread roll-over	37
6.5.5	Detection of damage to chamfered corner and flange	37
6.5.6	Detection of damage resulting from identification markings	37
6.5.7	Detection of defects on the external and internal face of the rim	37
6.5.8	Verification of web integrity	37
6.5.9	Verification of hub integrity	37
6.5.10	Verification of rim integrity - Detection of deep sub-surface tread defects	38
6.5.11	Detection of thermal defects on the web of a wheel used as a braking surface	38
6.5.12	Detection of overheating affecting the wheel rim-web transition on monobloc wheels	38
6.5.13	Verification of axle surface integrity	38
6.5.14	Detection of damage caused by corrosion	41
6.5.15	Detection of circumferential defects around the whole circumference	41
6.5.16	Detection of circumferential defects in a singular section of the circumference	41
6.5.17	Detection of notches and impact damage	41
6.5.18	Detection of longitudinal defects on axles	41
6.5.19	Detection of damage in interference fit zones	41
6.5.20	Verification after rectification	41
6.5.21	Verification of residual magnetism	41
6.5.22	Lubrication operation	41
6.5.23	Checking for axlebox defects	42
6.5.24	Verification of wheelset electrical resistance after heavy maintenance of wheelsets	42
6.6	Requirements for additional maintenance equipment and operations	42
7	In-service wheelset maintenance	42
7.1	Maintenance plan	42
7.2	Wheelset protection during vehicle and bogie cleaning	42
8	Off-vehicle wheelset maintenance	43
8.1	Maintenance plan	43
8.2	Key operations for off-vehicle wheelset maintenance	43
8.3	Off-vehicle wheelset cleaning	44
8.4	NDT Interval	44
9	Action to be taken on any wheelset after an incident in service or when not covered by the maintenance plan	44
9.1	Wheelset bearings subject to water ingress	44
9.2	Wheelsets having been subjected to a short circuit current (e.g. from falling overhead line equipment, etc.)	44
9.3	Detection of a wheel circularity defect by a trackside facility or an onboard monitoring system	44
9.4	Wheelsets loaded over the allowed limit	44
9.5	Hot axlebox detection	45
9.5.1	General	45
9.5.2	Technical procedure	45
9.6	Derailment	45
9.7	Head-on collision	46
9.8	Lubricant leakage or loss from the axlebox	46
9.9	Thermal overloaded wheels, brake incident (detection of seized brake or discoloration) ..	46
9.10	Reporting after detection of a wheelset irregularity outside the maintenance plan	46
10	Equipment not subject to Directive (EU) 2016/797	46
11	Summary table of requirements of this document	46
Annex A (normative)	Minimum database content for freight wagon wheelset traceability	47

A.1	Data categories for storage time	47
A.2	Minimum data to be collected	47
A.3	Measures to be applied resulting from lack of traceability	52
Annex B (informative) Database content for the traceability of wheelsets of vehicles in the scope of TSI "Rolling stock - Locomotive and passenger rated vehicles" (TSI Loc and Pas)		54
B.1	Data categories for storage time	54
B.2	Minimum data to be collected	54
B.3	Measures to be applied resulting from lack of traceability	59
Annex C (normative) Definition and illustration of defects		61
C.1	General	61
C.2	Defects for all types of wheel	61
C.3	Defects specific to wheel types	83
C.4	Axle defects	87
C.5	Axlebox defects	92
C.6	Wheelset defects	93
Annex D (normative) Freight stock		96
Annex E (informative) Rim size without roll-over for equipment not subject to Directive (EU) 2016/797		97
Annex F (normative) Definitions of Type A and B axles		98
Annex G (informative) Permissible circularity defects		101
Annex H (informative) Tyred wheels and resilient wheels		102
H.1	General	102
H.2	Marking of tyred wheels and resilient wheels	102
H.3	Tyre thickness of tyred wheels	103
H.4	Defects specific to tyred wheels	104
H.5	Verification of the electrical resistance during medium and heavy maintenance	104
Annex I (normative) Reference images for axle surface condition limits for off-vehicle wheelset maintenance		105
I.1	General	105
I.2	Local and severe defect	105
I.3	Large and heavily corroded areas, strongly and uniformly pitted surface	106
I.4	Corrosion defects in abutment area and transition radii	106
Annex J (informative) NDT interval		108
J.1	General	108
J.2	Axle	108
J.3	Wheel	108
Annex K (informative) Summary of the requirements of this standard for in-service boxed wheelsets		109
Annex L (informative) Characteristics of narrow gauge wheelsets		111
Annex M (informative) Characteristics of Spanish and Portuguese gauge wheelsets		112
Annex N (informative) Characteristics of Finnish and Baltic country gauge wheelsets		113
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive (EU) 2016/797 aimed to be covered		114
Bibliography		116