

DIN EN 15839:2024-12 (E)

Railway applications - Testing and simulation for the acceptance of running characteristics of railway vehicles - Running safety under longitudinal compressive force

Contents		Page
European foreword		4
Introduction		6
1	Scope	7
2	Normative references	8
3	Terms and definitions	8
4	Deviations from requirements	10
5	Proof of the endurable longitudinal compressive force	10
5.1	Assessment of endurable longitudinal compressive force	10
5.2	Required endurable longitudinal compressive force for use in conventional trains 10 5.3 Assessment of endurable longitudinal compressive force for use in high-capacity trains	11
5.4	Assessment of endurable longitudinal compressive force for vehicles equipped with centre couplers	11
5.5	Special vehicle layout	11
5.5.1	Permanently coupled units consisting of 2-axle wagons with standard ends or diagonal buffers	11
5.5.2	Permanently coupled units with bar couplers	12
Annex A (normative) Symbols		13
Annex B (normative) Conditions for the execution and evaluation of propelling tests for the determination of the endurable longitudinal compressive force of vehicles with side buffers		14
B.1	Test track	14
B.2	Test train	14
B.2.1	Standard configuration	14
B.2.2	Supplementary configuration for 2-axle vehicles with LoB 15,75 m	16
B.3	Execution of the tests	16
B.4	Measured values	17
B.4.1	Measurements during the tests	17
B.4.2	Other measurements	18
B.5	Used criteria for the evaluation of the endurable longitudinal compressive force	18
B.6	Analysis	18
B.7	Documentation of results	19
B.7.1	General	19
B.7.2	Characteristics of the track on which the tests were carried out	20
B.7.3	Characteristics of the test vehicle	20
B.7.4	Test results	20
Annex C (informative) Vehicles incorporated in conventional trains: Conditions for dispensation from the assessment of running safety under longitudinal compressive force		21
C.1	General	21

C.2	2-axle wagons	21
C.3	Wagons with two 2-axle bogies	23
C.4	Wagons with 3-axle bogies	26
C.5	Railbound construction and maintenance machines	27
Annex D	(informative) Conventional trains: Design characteristics of standardized interfaces of permanent coupled units for dispensation from the assessment of running safety under longitudinal compressive force - Specification of interface with diagonal buffers	29
Annex E	(informative) Requirements for the use of simulations as proof for endurable longitudinal compressive force	30
E.1	Introduction	30
E.2	State of the art for the heavy rail system in ENs related to running dynamics	30
E.3	Modelling for simulations	30
E.3.1	General	30
E.3.2	Intermediate wagons and trailing flanking wagon	31
E.3.3	Leading flanking wagon	32
E.3.4	Test track	32
E.4	Validation of the model	32
E.5	Performance of simulations	33
E.5.1	Required parameters (friction, track, speed etc)	33
E.5.2	Criteria applied for evaluation	33
Annex F	(informative) Scenarios for the assessment of endurable longitudinal compressive force of a vehicle incorporated in a high-capacity train	34
Annex G	(informative) Vehicle incorporated in a high-capacity trains: conditions for dispensation from the assessment of running safety under longitudinal compressive force	36
G.1	Introduction	36
G.2	Wagons with 2 bogies	36
G.3	Articulated wagons with 3 bogies	37
Annex H	(informative) Vehicles with centre couplers	38
Bibliography	39