DIN EN 17997:2025-04 (E)

Railway applications - Braking - Definition of ETCS brake curve parameters for Gamma trains

Contents

Page

European foreword 6

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms, definitions, symbols and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Symbols and abbreviated terms 10

4 ETCS on-board brake model parameters 11
4.1 ETCS on-board emergency brake model parameters 11
4.1.1 Nominal emergency brake deceleration Anominal 11
4.1.2 Correction factor Kdry(C,V,EBCL) 11
4.1.3 Correction factor Kwet(C,V) 12
4.1.4 Emergency brake response time 12
4.1.5 Traction cut-off time 12
4.2 ETCS on-board service brake model parameters 12
4.2.1 General 12
4.2.2 Nominal service brake deceleration AnominalSB 12
4.2.3 Service brake response time 12
4.2.4 Normal service brake deceleration and correction factors Kn 12

5 Brake system architecture model 13
5.1 General 13
5.2 General procedure description for Kdry(C,V,EBCL) determination 14
5.2.1 General 14
5.2.2 Step 1: Bottom-up functional analysis 14
5.2.3 Step 2: Top-down impact analysis 16
5.2.4 Step 3: Model simplification 17
5.3 Mathematical model building 18

6 Input data 20
6.1 General 20
6.2 Origin of input data 20
6.3 Validity of input data 21

7 Determination of ETCS emergency brake model parameters 22
7.1 Parameters 22
7.1.1 General 22
7.1.2 ETCS brake parameters set approaches 24
7.1.3 Approach dependency 25
7.1.4 Resolution of ETCS brake parameters 26
7.2 Nominal emergency brake deceleration 26
7.2.1 General 26
7.2.2 Determination by dynamic brake testing 27
7.2.3 Determination by calculation 33
7.2.4 Determination at degraded conditions 34
7.2.5 Determination for multiple unit operation 34

7.3 Correction factor Kdry(C,V,EBCL) ... 35
7.3.1 General ... 35
7.3.2 Determination of weighting factors j(C,V) ... 37
7.3.3 Determination of factors j(i,C,V) ... 37
7.3.4 Determination of factors 'k(C,V) and 'k(C,V) ... 39
7.3.5 Determination of correction factor Kdry(C,V,EBCL) with Monte Carlo method ... 40
7.4 Correction factor Kwet(C,V) ... 40
7.4.1 General method for determination of Kwet(C,V) ... 40
7.4.2 Determination of Kwet(C,V) for wheel/rail adhesion independent brake units ... 41
7.5 Emergency brake time characteristic ... 42
7.5.1 General ... 42
7.5.2 Multiple units operation ... 42
7.6 Traction cut-off time ... 43
7.6.1 General ... 43
7.6.2 Multiple units operation ... 44

8 Determination of ETCS service brake model parameters ... 44
8.1 General ... 44
8.2 Nominal deceleration for service braking ... 44
8.3 Service brake response time ... 44
8.4 Normal service brake deceleration and correction factors Kn ... 44

9 Common set of parameters ... 45

10 Validation of the calculation tool ... 45
10.1 General ... 45
10.2 Verification using a simplified model ... 46
10.3 Validation by example calculations ... 46

11 Documentation ... 47
11.1 General ... 47
11.2 Brake system architecture model ... 47
11.3 Input data ... 47
11.4 Nominal values ... 47
11.5 Correction factors ... 48
11.6 Source list ... 48

Annex A (informative) Basic formulae for the commonly used types of brake unit ... 49

A.1 General ... 49
A.2 Factor j(i,C,V) ... 49
A.2.1 Internal and external parameters for tread brake unit ... 49
A.2.2 Internal and external parameters for disc brake unit ... 51
A.2.3 Internal and external parameters for magnetic track brake unit ... 53
A.2.4 Internal and external parameters for eddy current brake unit ... 54
A.2.5 Internal and external parameters for electro-dynamic brake ... 57
A.3 Factor j'(i,C,V) ... 58

Annex B (informative) Derivation of the formulae for Kdry(C,V,EBCL) ... 60

B.1 General ... 60
B.2 Linear and nonlinear input variables ... 60
B.3 Consideration of the complete train ... 62
B.4 Consideration of the structure of the train and subsystem ... 63
B.4.1 General ... 63
B.4.2 Higher level structure of the train and subsystem ... 63
B.4.3 Structure of the control units without redundancies ... 65
B.4.4 Consideration of redundancies ... 66
B.4.5 Cross system variables ... 68

Annex C (normative) Application of Kdry(C,V,EBCL) formulae ... 71

C.1 General 71
C.2 Example 1: 3-car EMU 72
C.2.1 Description of the train 72
C.2.2 Brake system architecture model 76
C.2.3 Weighting factors 76
C.2.4 Determination of factors j(i,C,V) 76
C.2.5 Ki(C,V) formulae 80
C.2.6 Results 81
C.3 Example 2: architecture defined in EN 14531-1 82
C.3.1 Description of the train 82
C.3.2 Brake system architecture model 85
C.3.3 Weighting factors 86
C.3.4 Determination of factors j(i,C,V) 87
C.3.5 Ki formulae 88
C.3.6 Results 89

Annex D (informative) Determination of Kdry(C,V,EBCL) using the Monte Carlo method depending on the number of Monte Carlo iterations 90

D.1 Definitions 90
D.2 Determination of Kdry(C,V,EBCL) depending on the number of Monte Carlo iterations 90
D.3 Examples 92

Annex E (informative) Methods for simplifying the brake system architecture model 93

E.1 General 93
E.2 Structure grouping 94
E.2.1 Serial structure 94
E.2.2 Parallel redundant structure 95
E.2.3 Parallel branched structure 96
E.2.4 Double failure in parallel branched structure 97
E.3 Simplification example 97
E.3.1 Example system 97
E.3.2 Double failure check 98
E.3.3 Grouping of parallel branched structure 99
E.3.4 Grouping of parallel redundant structure 100
E.3.5 Grouping of serial structure 102
E.4 Extended description of the methods mentioned in 5.2.4 103
E.4.1 S-1 Grouping of components and technical functions 103
E.4.2 S-2 "Worst case consideration" 104
E.4.3 S-3 Neglection of highly improbable event 105
E.4.4 S-4 Reduction of model levels 105
E.4.5 S-5 Assumption of permanently failed components 106

Annex F (informative) Determination of the failure probability by FIT rate analysis 107

F.1 General 107
F.2 Conversion of FIT rates into failure probability 107

Annex G (informative) Simplified model, used for the validation of a calculation tool 108

G.1 General 108
G.2 Train model 108
G.2.1 General 108
G.2.2 Statistical data for pneumatic brake 111
G.2.3 Statistical data for magnetic track brake 112
G.2.4 Statistical data for electro-dynamic brake 112
G.2.5 Statistical data for traction units 113
G.3 Examples of validation of the correct use of parameter information 113
G.3.1 Mass deviation 113
G.3.2 Wheel diameter deviation 113
G.3.3 MTB brake force deviation 114

G.3.4 ED brake force deviation 114
G.3.5 Failure probability of traction cut-off 115
G.4 Example of verification of the correct use of structural information 115
G.4.1 Failure probability on bogie level for pneumatic brake 115
G.4.2 Failure probability on vehicle type level for MTB 115

Bibliography 117