

# DIN EN 16584-1:2025-12 (E)

## Railway applications - Design for PRM use - General requirements - Part 1: Contrast

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		6
<b>1</b>	<b>Scope .....</b>	<b>7</b>
<b>2</b>	<b>Normative references .....</b>	<b>8</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>8</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>13</b>
<b>5</b>	<b>Requirements and assessment .....</b>	<b>14</b>
5.1	General .....	14
5.2	Infrastructure .....	14
5.2.1	Obstacle-free routes .....	14
5.2.2	Doors and entrances .....	14
5.2.3	Transparent obstacles .....	16
5.2.4	Furniture and free-standing devices .....	16
5.2.5	Handrails .....	16
5.2.6	Platform danger area and edge of platform .....	16
5.2.7	End of platform .....	17
5.3	Rolling stock .....	17
5.3.1	Seats .....	17
5.3.2	Doors .....	19
5.3.3	Exterior doors .....	20
5.3.4	Interior doors .....	23
5.3.5	Toilets (standard and universal) .....	24
5.3.6	Customer Information .....	26
5.3.7	Height changes .....	29
5.3.8	Handrails .....	30
5.3.9	Access/egress steps .....	30
5.3.10	Call for aid devices .....	31
5.3.11	Boarding aids .....	31
<b>6</b>	<b>Methodologies for assessing contrast .....</b>	<b>32</b>
6.1	General .....	32
6.2	Establishing LRVs .....	33
6.2.1	General .....	33
6.2.2	Method of establishing LRV .....	33
6.2.3	Specific assessment criteria for stainless steel .....	38
6.3	Method of assessing contrast with LRVs established (as in 6.2) .....	39
6.3.1	General requirements for contrast .....	39
6.3.2	Specific requirements for contrast on signage .....	39
6.3.3	Durability of contrast .....	39
6.3.4	Specific requirements for electronic display .....	40
<b>Annex A (normative) Contrast Charts .....</b>		<b>41</b>
A.1	General .....	41
A.2	Worked examples for contrast .....	43
A.3	Self-contrasting bands .....	45

<b>Annex B (normative) Contrast for doors and transparent obstacles .....</b>	<b>46</b>
<b>B.1 General .....</b>	<b>46</b>
<b>B.2 Exterior doors .....</b>	<b>46</b>
<b>B.3 Case 1: If the window is less than or equal to 40 % of the visible door leaf .....</b>	<b>46</b>
<b>B.4 Case 2: If the window is greater than 40 % of the visible door leaf .....</b>	<b>48</b>
<b>B.5 Case 3: Alternative if the door leaf is not coloured to contrast with the bodyside .....</b>	<b>49</b>
<b>B.6 Markings for interior doors or transparent obstacles .....</b>	<b>49</b>
<b>Annex C (normative) Effective contrast calculation for displays .....</b>	<b>52</b>
<b>C.1 Illuminated displays .....</b>	<b>52</b>
<b>C.2 Back lit and/or self-lit displays .....</b>	<b>52</b>
<b>Annex D (informative) Supporting information from published documents .....</b>	<b>54</b>
<b>D.1 General .....</b>	<b>54</b>
<b>D.2 CIE Publication 196:2011 CIE Guide to Increasing Accessibility in Light and Lighting .....</b>	<b>54</b>
<b>D.3 ADA (Americans with Disabilities Act) Accessibility Guidelines for Buildings and Facilities .....</b>	<b>54</b>
<b>D.4 BS 8300-2 2018 Design of an Accessible and Inclusive Built Environment Part 2 Buildings - Code of practice .....</b>	<b>54</b>
<b>Annex ZA (informative) Relationship between this European Standard and the Essential requirements of EU Directive (EU) 2016/797 aimed to be covered .....</b>	<b>56</b>
<b>Bibliography .....</b>	<b>59</b>