

DIN EN 16586-1:2025-11 (E)

Railway applications - Design for PRM use - Accessibility of persons with reduced mobility to rolling stock - Part 1: Steps for access and egress

Contents		Page
European foreword		3
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Symbols and abbreviations	8
5	Requirements and assessment	9
5.1	General	9
5.2	Step position for vehicle access and egress	9
5.2.1	General requirements	9
5.2.2	Access/egress steps	9
Annex A (normative) Calculations for step location		14
A.1	General	14
A.2	Values to be used for calculating step position for vehicle access and egress	14
A.2.1	General	14
A.2.2	Rolling stock intended to stop, in normal operation, at platforms of 550 mm height	15
A.2.3	Rolling stock intended to stop, in normal operation, at platforms of 760 mm height	15
A.2.4	Rolling stock intended to stop, in normal operation, at both platforms of 760 mm height and platforms of 550 mm height, and having two or more access steps	15
A.2.5	The measuring point for stepping up into the vehicle or stepping down into the vehicle ...	15
Annex B (normative) Step nose		18
Annex ZA (informative) Relationship between this European Standard and the essential requirements of EU Directive (EU) 2016/797 aimed to be covered		19
Bibliography		21