

DIN EN 15273-1:2026-09 (E)

Railway applications - Gauges - Part 1: General - Common rules for rolling stock and infrastructure

Contents

Page

European foreword	5
Introduction	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	8
4 Symbols and abbreviations	18
4.1 Common symbols	18
4.2 Specific symbols for absolute and comparative gauging processes	28
5 Approaches to gauging	31
5.1 Railway gauging processes	31
5.2 How to use EN 15273 series	32
5.3 Choosing a defined gauge or a gauging process	33
5.3.1 Interoperability between Railway Undertaking and Infrastructure Manager	33
5.3.2 Defined gauging methods	34
5.3.3 Absolute gauging process	36
5.3.4 Comparative gauging process	37
6 Elements involved in a gauging process	37
6.1 General diagram in the lateral direction	37
6.2 General diagram in the vertical direction	38
7 Gauges and gauging process	39
7.1 Defined gauges by calculation	39
7.1.1 Basic elements of the defined gauges	39
7.1.2 Reference profile and associated rules	41
7.2 Absolute and comparative gauging process	42
7.2.1 General	42
7.2.2 Absolute gauging process	43
7.2.3 Comparative gauging process	46
Annex A (normative) Specific considerations for the classic calculations of defined gauges	48
A.1 In the lateral direction	48
A.1.1 Geometric overthrow due to the bogie	48
A.1.2 Geometric overthrow due to the carbody	48
A.1.3 Clearance between the wheelsets and the carbody	49
A.1.4 Clearance between the wheelsets and the track	49
A.1.5 Roll	50
A.1.6 Lateral displacement of the track	57
A.2 In the vertical direction	57
Annex B (normative) Defined kinematic gauges	59
B.1 General	59
B.2 In the lateral direction	60

B.2.1	Inside the kinematic reference profile	60
B.2.2	Outside the kinematic reference profile	62
B.3	In the vertical direction	64
B.3.1	Inside the kinematic reference profile	64
B.3.2	Outside the kinematic reference profile	65
B.4	Pantograph gauge	65
B.4.1	General principle	65
B.4.2	In the lateral direction	66
B.4.3	In the vertical direction	69
B.5	Lower parts	71
B.6	Wheel and rail area	73
B.6.1	General	73
B.6.2	Zone swept by the wheel	73
B.6.3	Position of the check-rails	75
B.7	Contact ramps	75
B.7.1	General	75
B.7.2	For the infrastructure	76
B.7.3	For the rolling stock	76
B.8	Stopping devices	77
B.9	Marshalling hump	78
B.9.1	General convention	78
B.9.2	Track brakes installed close to the marshalling humps	78
B.10	Access to ferries	81
B.10.1	General Principle	81
B.10.2	Passing over link spans onto ferries	81
Annex C (normative) Defined static gauges		82
C.1	General	82
C.2	In the lateral direction	82
C.2.1	Inside the static reference profile	82
C.2.2	Outside the static reference profile	83
C.3	In the vertical direction	83
C.3.1	Inside the static reference profile	83
C.3.2	Outside the static reference profile	83
Annex D (normative) Defined dynamic gauges		85
D.1	General	85
D.2	In the lateral direction	86
D.2.1	Inside the dynamic reference profile	86
D.2.2	Outside the dynamic reference profile	87
D.3	In the vertical direction	88
D.3.1	Inside the dynamic reference profile	88
D.3.2	Outside the dynamic reference profile	89
D.4	Pantograph area	89
D.4.1	General principle	89
D.4.2	In the lateral direction	89
D.4.3	In the vertical direction	90
D.5	Lower parts	91
D.5.1	General	91
D.5.2	Wheel and rail area	91
D.5.3	Stopping devices	91
D.5.4	Marshalling hump	92
D.5.5	Access to ferries	92
Annex E (normative) The absolute gauging process		93
E.1	Brief background	93
E.2	Basic principles	93
E.2.1	General	93
E.2.2	Gauging compatibility	94

E.2.3	Generic throw calculation for absolute and comparative process	95
E.3	Elements of the gauging process	96
E.3.1	Lateral direction	96
E.3.2	Vertical direction	97
E.3.3	Passing clearances (Clearance between vehicles on adjacent tracks)	99
E.3.4	Clearance categories	100
E.3.5	Electrical clearances	101
E.3.6	Pantograph sway	101
E.3.7	Electrification compatibility	102
E.3.8	Cross-level variation	103
Annex F (normative) The comparative gauging process		104
F.1	Background	104
F.2	Basic principles	104
F.2.1	General	104
F.2.2	Gauging compatibility	105
F.2.3	Computer simulation	106
F.3	Gauging process	106
F.3.1	Virtual route	106
F.3.2	Swept envelope calculation	106
F.3.3	Comparison of swept envelopes	107
Annex G (informative) Compatibility between static and kinematic defined gauges		108
Annex H (normative) Steps for access and egress - Location and gaps with platform for defined gauge		111
H.1	General	111
H.2	For the rolling stock	111
H.2.1	Principles	111
H.2.2	Location inside an area	111
H.2.3	Maximum gaps	113
H.2.4	Checking of horizontal location	114
H.2.5	Horizontal location inside an area	116
H.2.6	Maximum horizontal gap	116
H.2.7	Checking of vertical location	116
H.2.8	Vertical location inside an area	117
H.2.9	Maximum vertical gap	117
H.3	Conventional platform position	117
H.3.1	General case	117
H.3.2	For rolling stock dedicated to run on specific national infrastructure	117
H.4	Conventional gaps	120
Bibliography		121