

DIN EN 14198:2026-05 (E)

Railway applications - Braking - Requirements for the brake system of trains hauled by locomotives

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 7 |
| 4 | Symbols and abbreviated terms | 9 |
| 5 | Requirements | 9 |
| 5.1 | General requirements of the train brake system | 9 |
| 5.2 | General safety requirements | 9 |
| 5.2.1 | Design principles | 9 |
| 5.2.2 | Fire protection | 11 |
| 5.2.3 | Environmental condition | 11 |
| 5.3 | Requirements of the main brake system | 11 |
| 5.3.1 | General requirements | 11 |
| 5.3.2 | General functions on train level | 12 |
| 5.3.3 | Additional requirements at the vehicle level | 18 |
| 5.4 | "EN-UIC" brake system - based on air brake system | 19 |
| 5.4.1 | General | 19 |
| 5.4.2 | General architecture | 20 |
| 5.4.3 | Brake subsystems | 20 |
| 5.4.4 | Functional requirements at train level | 24 |
| 5.4.5 | Design requirements | 37 |
| 5.4.6 | Brake functions at vehicle level | 38 |
| 5.4.7 | Brake system related markings | 41 |
| 5.5 | Direct EP brake control | 41 |
| 5.6 | Additional brake systems | 41 |
| 5.6.1 | Independent dynamic brake system | 41 |
| 5.6.2 | Independent direct brake | 42 |
| 5.7 | Brake management | 44 |
| 5.7.1 | Brake blending at vehicle level | 44 |
| 5.7.2 | Manual mode | 45 |
| 5.7.3 | Brake blending at train level | 45 |
| 5.7.4 | Jerk/ramps | 46 |
| 5.8 | Wheel slide protection | 46 |
| 5.9 | Compressed air supply | 47 |
| 5.9.1 | General requirements | 47 |
| 5.9.2 | Capacity | 48 |
| 5.9.3 | Air quality | 48 |
| 5.10 | Enhancement of wheel/rail adhesion | 48 |
| 6 | Performance | 49 |
| 6.1 | General aspects | 49 |
| 6.2 | Performance calculation | 50 |
| 6.2.1 | General | 50 |
| 6.2.2 | Calculations for nominal mode | 51 |
| 6.2.3 | Equivalent response and delay time | 52 |
| 6.2.4 | Calculations for degraded mode | 52 |

| | | |
|---|--|----|
| 6.2.5 | Calculations for degraded conditions | 52 |
| 6.3 | Relevant load conditions | 53 |
| 6.3.1 | Locomotives | 53 |
| 6.3.2 | Coaches | 53 |
| 6.3.3 | Wagons | 53 |
| 6.4 | Service braking | 53 |
| 6.5 | Thermal capacity | 54 |
| 6.6 | Adhesion | 55 |
| 6.6.1 | General requirements | 55 |
| 6.6.2 | Emergency brake application | 55 |
| 6.6.3 | Service brake application | 55 |
| 6.7 | Parking brake performance | 56 |
| 6.7.1 | General | 56 |
| 6.7.2 | Static efficiency of rigging | 56 |
| 6.7.3 | Activation force | 56 |
| Annex A (normative) Vehicle requirements | | 57 |
| Annex B (informative) Train related brake performance categories | | 61 |
| Annex C (informative) Explanation of "proven design" concept | | 65 |
| Annex D (informative) Corresponding standards EN - UIC | | 66 |
| Annex E (normative) Brake pipe pressure control system | | 68 |
| E.1 | General requirements | 68 |
| E.2 | Release position | 69 |
| E.3 | Service brake application | 70 |
| E.4 | Emergency brake application | 70 |
| E.5 | Overcharge function | 71 |
| E.6 | Quick release function | 72 |
| Annex F (normative) Venting performance of emergency valves | | 76 |
| F.1 | Purpose | 76 |
| F.2 | General rules | 76 |
| F.3 | Test procedure | 76 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive (EU) 2016/797 aimed to be covered | | 78 |
| Bibliography | | 82 |