DIN EN 13848-6:2026-10 (E)

Railway applications - Track - Track geometry quality - Part 6: Characterization of track geometry quality

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviations 5
3.1 Terms and definitions 5
3.2 Symbols and abbreviations 6

4 General principles 6
4.1 Introduction 6
4.2 Parameters for track geometry quality assessment 7
4.3 Transparency 7
4.4 Complexity 7
4.5 Track-vehicle interaction 7

5 Methods of assessment of track geometry quality 7
5.1 General 7
5.2 Reference method: TQIref - Standard deviation (SD) 7
5.3 Other methods 8
5.3.1 General 8
5.3.2 Number of isolated defects 8
5.3.3 Combined standard deviation (CoSD) 9
5.3.4 Standard deviation of the combinations of parameters 9
5.3.5 Point mass acceleration method (PMA) 10
5.3.6 Methods based on vehicle response 11
5.3.7 Power spectral density (PSD) 12

6 Levels of aggregation and calculation methods 13

7 Classes of track geometry quality 13
7.1 General 13
7.2 Description of track quality classes (TQC) 13
7.3 Values of track quality classes 15
7.4 Assignment of TQCs 16
7.5 Possible application of TQCs 16

Annex A (informative) Point mass acceleration method (PMA) 18

A.1 Introduction 18
A.2 Calculation of the PMA-assessment figure 18

Annex B (informative) Vehicle response analysis methods (VRA) 20

B.1 Introduction 20
B.2 Determination of the assessment tables 20
B.3 Application of the assessment tables 24

Annex C (normative) Method for calculating reference TQIs (TQIref) 27

C.1 Introduction 27
C.2 Description of the method 27

Annex D (informative) Method of classification of alternative TQI using the TQCs 28

D.1 Introduction 28
D.2 Description of the conversion method 28

Bibliography 30