

# DIN EN 13262:2006-01 (E)

## Railway applications - Wheelsets and bogies - Wheels - Product requirements

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Product definition .....</b>	<b>7</b>
<b>3.1</b>	<b>Chemical composition .....</b>	<b>7</b>
<b>3.1.1</b>	<b>Values to be achieved .....</b>	<b>7</b>
<b>3.1.2</b>	<b>Location of the sample .....</b>	<b>7</b>
<b>3.1.3</b>	<b>Chemical analysis .....</b>	<b>7</b>
<b>3.2</b>	<b>Mechanical characteristics .....</b>	<b>7</b>
<b>3.2.1</b>	<b>Tensile test characteristics .....</b>	<b>7</b>
<b>3.2.2</b>	<b>Hardness characteristics in the rim .....</b>	<b>9</b>
<b>3.2.3</b>	<b>Impact test characteristics .....</b>	<b>10</b>
<b>3.2.4</b>	<b>Fatigue characteristics .....</b>	<b>11</b>
<b>3.2.5</b>	<b>Toughness characteristic of the rim .....</b>	<b>11</b>
<b>3.3</b>	<b>Heat treatment homogeneity .....</b>	<b>13</b>
<b>3.3.1</b>	<b>Values to be achieved .....</b>	<b>13</b>
<b>3.3.2</b>	<b>Test pieces .....</b>	<b>13</b>
<b>3.3.3</b>	<b>Test method .....</b>	<b>13</b>
<b>3.4</b>	<b>Material cleanliness .....</b>	<b>13</b>
<b>3.4.1</b>	<b>Micrographic cleanliness .....</b>	<b>13</b>
<b>3.4.2</b>	<b>Internal integrity .....</b>	<b>14</b>
<b>3.5</b>	<b>Residual stresses .....</b>	<b>17</b>
<b>3.5.1</b>	<b>3.5.2 Values to be achieved .....</b>	<b>17</b>
<b>3.5.3</b>	<b>Test piece .....</b>	<b>18</b>
<b>3.5.4</b>	<b>Measurement methods .....</b>	<b>18</b>
<b>3.6</b>	<b>Surface characteristics .....</b>	<b>18</b>
<b>3.6.1</b>	<b>Surface appearance .....</b>	<b>18</b>
<b>3.6.2</b>	<b>Surface integrity .....</b>	<b>19</b>
<b>3.7</b>	<b>Geometric tolerances .....</b>	<b>19</b>
<b>3.8</b>	<b>Static imbalance .....</b>	<b>22</b>
<b>3.9</b>	<b>Protection against corrosion .....</b>	<b>22</b>
<b>3.10</b>	<b>Manufacturer's marking .....</b>	<b>23</b>
<b>Annex A (normative) Control of the hydrogen content in the steel for solid wheels at the melting stage .....</b>		<b>24</b>
<b>A.1</b>	<b>Sampling .....</b>	<b>24</b>
<b>A.2</b>	<b>Analysis methods .....</b>	<b>24</b>
<b>A.3</b>	<b>Precautions .....</b>	<b>24</b>
<b>Annex B (informative) Example of test method for the determination of fatigue characteristics .....</b>		<b>25</b>
<b>B.1</b>	<b>Test piece .....</b>	<b>25</b>
<b>B.2</b>	<b>Test rig .....</b>	<b>25</b>
<b>B.3</b>	<b>Test monitoring .....</b>	<b>25</b>
<b>B.4</b>	<b>Analysis of results .....</b>	<b>25</b>
<b>Annex C (informative) Strain gauge method for determining the variations of circumferential residual stresses located deep under the tread (Destructive method) .....</b>		<b>26</b>
<b>C.1</b>	<b>Principle of the method .....</b>	<b>26</b>

C.2	Procedure .....	26
C.3	Calculation of the variation of the circumferential residual stress located deep under the tread .....	27
Annex D (informative)	Ultrasonic method for determining the residual stresses in the rim (non-destructive method) .....	32
D.1	Introduction .....	32
D.2	Method of measurement .....	32
D.3	Evaluation of results .....	33
Annex E (informative)	Product qualification .....	34
E.1	General .....	34
E.2	Requirements .....	34
E.3	Qualification procedure .....	35
E.4	Qualification certificate .....	37
E.5	Qualification file .....	38
Annex F (informative)	Product delivery .....	39
F.1	General .....	39
F.2	Delivery condition .....	39
F.3	Controls on each wheel .....	40
F.4	Batch control .....	40
F.5	Quality plan .....	43
F.6	Allowable rectification .....	43
Annex ZA (informative)	Clauses of this European Standard addressing essential requirements or other provisions of EU Directives .....	44
Bibliography	.....	46