DIN EN 13715:2006-05 (E)

Railway applications - Wheelsets and bogies - Wheels - Tread profile

Contents

Page

Foreword 3

Introduction 3

1 Scope 4

2 Normative references 4

3 Definition of the tread profile 4

4 Symbols and abbreviations 6
4.1 Definition of the profiles 7

5 Construction method 7
5.1 Definition of the axes 7
5.2 Base profile 7
5.3 Profile construction 7
5.3.1 Profile zone H2 - D1 (flange) 7
5.3.2 Profile connection zone D1 - C1 8
5.3.3 Profile zone D1 - C1 -D0 for flange thicknesses 28,5 mm e 32,5 mm 9
5.3.4 Zone D0 - B1 (B1a or B1b) 10
5.3.5 Reverse slope and chamfer 11

6 Geometric characteristics 11
6.1 R20,5 connecting radius 11
6.2 RE and RI 12 mm connecting radii 11
6.3 Rfa connecting radius 12
6.4 R13 connecting radius 12
6.5 Wheel tread 12
6.6 Reverse slope - Chamfer 12

7 Profile designation 12

8 Reference equipment for verification of the wheel profile 12

Annex A (normative) Flange 13

A.1 Definition of the flange 13
A.2 Flange geometry 14

Annex B (normative) 1/40th profile 15

B.1 Complete reference profile: construction with a 32,5 mm thick flange and 15 % reverse slope 15
B.2 Profile construction: specific zones 15

Annex C (normative) S1002 profile 17

C.1 Complete reference profile: construction with 32,5 mm thick flange and 6,7 % reverse slope 17
C.2 Profile construction: specific zones 17

Annex D (normative) EPS profile **21**

D.1 Complete reference profile: construction with 32,5 mm thick flange and 10 % reverse slope **21**
D.2 Profile construction: specific zones **21**

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 96/48/EC **24**

Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2001/16/EC **26**

Bibliography **28**