

# DIN EN 13803-2:2008-04 (E)

Railway applications - Track - Track alignment design parameters - Track gauges 1435 mm and wider - Part 2: Switches and crossings and comparable alignment design situations with abrupt changes of curvature (includes Corrigendum AC:2007)

---

| <b>Contents</b> |  | <b>Page</b> |
|-----------------|--|-------------|
| Foreword .....  |  | 4           |
| <b>1</b>        | <b>Scope .....</b>   | <b>5</b>    |
| <b>2</b>        | <b>Normative references .....</b>  | <b>5</b>    |
| <b>3</b>        | <b>Terms and definitions .....</b>   | <b>5</b>    |
| <b>4</b>        | <b>Symbols and abbreviations .....</b>   | <b>6</b>    |
| <b>5</b>        | <b>General requirements .....</b>  | <b>7</b>    |
| <b>6</b>        | <b>Principles for the assessment of abrupt changes of cant deficiency at abrupt changes in curvature .....</b>                                 | <b>8</b>    |
| <b>6.1</b>      | <b>General .....</b>   | <b>8</b>    |
| <b>6.2</b>      | <b>Principle based on limiting values of abrupt change of cant deficiency (I) .....</b>  | <b>8</b>    |
| <b>7</b>        | <b>Circular curves without transition curves .....</b>   | <b>8</b>    |
| <b>7.1</b>      | <b>Limiting values based on the principle of abrupt change of cant deficiency <math>l_{lim}</math> .....</b>                                   | <b>8</b>    |
| <b>7.1.1</b>    | <b>General .....</b>   | <b>8</b>    |
| <b>7.1.2</b>    | <b>Switch and crossing layouts .....</b>   | <b>9</b>    |
| <b>7.1.3</b>    | <b>Plain line .....</b>  | <b>10</b>   |
| <b>7.2</b>      | <b>Limiting values based on the principle of the virtual transition .....</b>  | <b>10</b>   |
| <b>7.3</b>      | <b>Minimum radius of horizontal curves .....</b>   | <b>10</b>   |
| <b>8</b>        | <b>Combinations of horizontal curves .....</b>   | <b>10</b>   |
| <b>8.1</b>      | <b>General .....</b>   | <b>10</b>   |
| <b>8.2</b>      | <b>Limiting length of intermediate element(s) between two abrupt changes of curvature (<math>L_{slim}</math>) .....</b>                        | <b>11</b>   |
| <b>8.3</b>      | <b>Abrupt change of cant deficiency (I) at abrupt changes in curvature in combined curves ..</b>   | <b>12</b>   |
| <b>8.3.1</b>    | <b>Length of intermediate element(s) equal to, or greater than the limiting minimum value (<math>L_s \geq L_{slim}</math>) .....</b>           | <b>12</b>   |
| <b>8.3.2</b>    | <b>Intermediate element(s) of sub-standard length (<math>L_s &lt; L_{slim}</math>) or no intermediate element (<math>L_s = 0</math>) .....</b> | <b>12</b>   |
| <b>8.4</b>      | <b>Requirements for preventing buffer locking .....</b>  | <b>13</b>   |
| <b>9</b>        | <b>Alignment rules and parameters for designing switch and crossing layouts .....</b>  | <b>14</b>   |
| <b>9.1</b>      | <b>General rules .....</b>   | <b>14</b>   |
| <b>9.1.1</b>    | <b>Horizontal alignment .....</b>  | <b>14</b>   |
| <b>9.1.2</b>    | <b>Vertical alignment .....</b>  | <b>14</b>   |
| <b>9.2</b>      | <b>Switch and crossing layouts in straight track without cant .....</b>  | <b>15</b>   |
| <b>9.2.1</b>    | <b>Simple turnout .....</b>  | <b>15</b>   |
| <b>9.2.2</b>    | <b>Turnouts with variable curvature .....</b>  | <b>15</b>   |
| <b>9.3</b>      | <b>Switch and crossing layouts installed on horizontal curves .....</b>  | <b>18</b>   |
| <b>9.3.1</b>    | <b>General rules .....</b>   | <b>18</b>   |
| <b>9.3.2</b>    | <b>Horizontal radii .....</b>  | <b>18</b>   |
| <b>9.3.3</b>    | <b>Cant D .....</b>  | <b>19</b>   |
| <b>9.3.4</b>    | <b>Cant deficiency I .....</b>   | <b>19</b>   |
| <b>9.3.5</b>    | <b>Cant excess E .....</b>   | <b>20</b>   |

|   |    |
|---|----|
| Annex A (informative) General design considerations .....   | 21 |
| Annex B (informative) The installation of switch and crossing layouts .....   | 22 |
| B.1 Standard switch and crossing units .....  | 22 |
| B.2 Lateral track resistance at the switch panel .....  | 22 |
| B.3 Stress transition zone between continuously welded track and jointed track .....  | 22 |
| B.4 Switch and crossing layouts on, or near under-bridges .....   | 23 |
| B.5 Limits for diamond crossings, diamond crossings with slips and tandem turnouts .....  | 23 |
| B.6 Switch and crossing layouts with steel bearers .....  | 23 |
| B.7 Abutting turnouts .....   | 23 |
| B.8 Crossovers and follow-on turnouts with reverse curves .....   | 23 |
| B.9 Scissors crossovers and single or double junctions .....  | 24 |
| B.10 Tracks with cant gradients .....   | 24 |
| B.11 Influence of cant on the deflection angle in the horizontal plane .....  | 24 |
| Annex C (normative) Rules for converting parameter values for track gauges wider than 1 435 mm  | 26 |
| C.1 Scope .....   | 26 |
| C.2 Symbols and abbreviations .....   | 26 |
| C.3 Basic hypothesis .....  | 26 |
| C.4 Conversion rules .....  | 27 |
| C.4.1 Application of I limiting values .....  | 27 |
| C.4.2 Cant .....  | 27 |
| C.4.3 Equilibrium cant .....  | 28 |
| C.4.4 Other formulas and values of the standard .....   | 28 |
| C.4.5 Annexes .....   | 29 |
| Annex D (informative) Limits of lateral acceleration .....  | 30 |
| D.1 Introduction .....  | 30 |
| D.2 Wheel-base effect .....   | 31 |
| D.3 Limiting values of the non-compensated lateral acceleration .....   | 31 |
| D.4 Conclusion .....  | 32 |
| Annex E (informative) The principle of virtual transition .....   | 33 |
| E.1 Virtual transition at an abrupt change of curvature .....   | 33 |
| E.2 Virtual transition at a short intermediate length between two abrupt changes of curvature .....   | 33 |
| E.3 Limiting values based on the principle of the virtual transition .....  | 34 |
| E.3.1 General .....   | 34 |
| E.3.2 Characteristic vehicle with a distance of 20 m between bogie centres .....  | 34 |
| E.3.3 Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres .....  | 35 |
| Annex F (informative) A method for calculating the maximum permissible speed at the toe of a non-tangential switch .....  | 36 |
| Annex G (informative) Constraints and risks associated with the use of maximum (or minimum) limiting values .....   | 38 |
| Annex H (informative) The maximum permissible speed of tilting body trains over switch and crossing layouts .....   | 39 |
| H.1 General .....   | 39 |
| H.2 The maximum permissible speeds over abrupt changes of curvature .....   | 39 |
| H.3 The permissible speeds over switch and crossing layouts on curves .....   | 39 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 96/48/EC of 23 July 1996 on the interoperability of the trans-European high-speed rail system amended by the EU Directive 2004/50/EC of 29 April 2004 ..... | 40 |
| Bibliography .....  | 41 |