

ISO 529:1993-01 (E)

Short machine taps and hand taps

Contents	Page
Section 1 General	1
1.1 Scope	1
1.2 Normative references	1
Section 2 ISO metric threads	3
2.1 Threads up to M25	3
2.1.1 Full-diameter shank taps with plain connecting portion	3
2.1.2 Full-diameter shank taps with recess	4
2.1.3 Relieved-shank taps	5
2.2 Threads above M25	7
2.2.1 Relieved-shank taps for coarse pitch metric thread	7
2.2.2 Relieved-shank taps for fine pitch metric thread	8
Section 3 ISO inch threads, "Unified coarse" (UNC) and "Unified fine" (UNF) series	11
3.1 "Unified" series threads up to 25,4 mm	11
3.1.1 Full-diameter shank taps with plain connecting portion	11
3.1.2 Full-diameter shank taps with recess	12
3.1.3 Relieved-shank taps	13
3.2 "Unified" series threads above 25,4 mm	14
3.2.1 Relieved-shank taps for "Unified coarse" series threads	14
3.2.2 Relieved-shank taps for "Unified fine" series threads	15
Section 4 Non-recommended inch threads	16
4.1 "British Standard Whitworth" (BSW) and "British Standard Fine" (BSF) threads	16
4.1.1 Full-diameter shank taps with recess	16
4.1.2 Relieved-shank taps	17
4.2 "British Association" (BA) threads	19
4.2.1 Full-diameter shank taps with plain connecting portion	19
4.2.2 Full-diameter shank taps with recess	20
4.2.3 Relieved-shank taps	21
Annexes	
A Shank diameter, overall length and thread length as a function of range of diameters and pitches	22
B Shank diameters and size of driving squares (Extract from ISO 237)	24
C Bibliography	25