

# ISO 5609-5:2012-12 (E)

## Tool holders for internal turning with cylindrical shank for indexable inserts - Part 5: Style U

---

| <b>Contents</b>           |  | <b>Page</b> |
|---------------------------|--|-------------|
| <b>Foreword</b> .....     |  | <b>iv</b>   |
| <b>1</b>                  | <b>Scope</b> .....   | <b>1</b>    |
| <b>2</b>                  | <b>Normative references</b> .....  | <b>1</b>    |
| <b>3</b>                  | <b>Dimensions</b> .....  | <b>1</b>    |
| <b>3.1</b>                | <b>General</b> .....   | <b>1</b>    |
| <b>3.2</b>                | <b>Tool holder, style U, for rhombic indexable insert, shape D</b> ..... | <b>2</b>    |
| <b>3.3</b>                | <b>Tool holder, style U, for rhombic indexable insert, shape V</b> ..... | <b>3</b>    |
| <b>4</b>                  | <b>Designation</b> .....   | <b>4</b>    |
| <b>5</b>                  | <b>Material</b> .....  | <b>5</b>    |
| <b>6</b>                  | <b>Design</b> .....  | <b>5</b>    |
| <b>6.1</b>                | <b>Type of tool</b> .....  | <b>5</b>    |
| <b>6.2</b>                | <b>Type of mounting</b> .....  | <b>5</b>    |
| <b>6.3</b>                | <b>Corner radius <math>r</math></b> .....                                | <b>5</b>    |
| <b>6.4</b>                | <b>Thickness, <math>s</math>, of insert</b> .....                        | <b>6</b>    |
| <b>7</b>                  | <b>Extent of delivery</b> .....  | <b>6</b>    |
| <b>8</b>                  | <b>Marking</b> .....   | <b>6</b>    |
| <b>Bibliography</b> ..... |  | <b>7</b>    |