

ISO 16462:2014-06 (E)

Cubic boron nitride inserts, tipped or solid - Dimensions, types

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Insert shapes and design | 1 |
| 3.1 | Insert shapes | 1 |
| 3.2 | Normal clearance n | 1 |
| 3.3 | Cutting edge corner | 1 |
| 3.4 | Tolerance class | 1 |
| 3.5 | Design of cutting edges | 2 |
| 3.6 | Insert type | 2 |
| 4 | Designation | 2 |
| 4.1 | General | 2 |
| 4.2 | Designation of inserts for turning | 2 |
| 4.3 | Designation of a tipped insert for milling | 2 |
| 5 | Dimensions | 3 |
| 5.1 | Insert shape T with fixing hole (inserts for turning) | 3 |
| 5.2 | Insert shape S with fixing hole (inserts for turning) | 4 |
| 5.3 | Insert shape C with fixing hole (inserts for turning) | 5 |
| 5.4 | Insert shape D with fixing hole (inserts for turning) | 6 |
| 5.5 | Insert shape V with fixing hole (inserts for turning) | 7 |
| 5.6 | Insert shape S with fixing hole (inserts for milling) | 8 |
| 5.7 | Insert shape C with fixing hole (inserts for milling) | 9 |
| 5.8 | Insert shapes C, R, S, and T without fixing hole (inserts for turning) | 9 |
| 5.9 | Insert shapes S and T without fixing hole (inserts for milling) | 11 |
| 5.10 | Insert shapes S and T without fixing hole (inserts for milling) | 12 |
| 5.11 | Insert shape W with fixing hole (inserts for turning) | 13 |
| 5.12 | Insert shape W without fixing hole (inserts for turning) | 14 |
| 6 | Cutting edge length, l_1, of tipped inserts | 15 |
| 6.1 | General | 15 |
| 6.2 | Inserts with radius | 15 |
| 6.3 | Inserts with wiper edge | 15 |
| 7 | Base material, cutting material | 16 |
| 8 | Measurements | 16 |
| 9 | Marking | 16 |