

DIN EN 13236:2016-05 (E)

Safety requirements for superabrasive products (includes Amendment A1:2015)

Contents		Page
European foreword		5
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms, definitions and symbols	8
3.1	General	8
3.2	Grinding machines	8
3.3	Grinding method	9
3.4	Type of application	9
3.5	Symbols	11
3.6	Other symbols	11
4	List of significant hazards	12
5	Safety requirements	12
5.1	General requirements	12
5.2	Requirements for precision superabrasive grinding and cutting-off wheels	13
5.2.1	Bore tolerances	13
5.2.2	Sequence of maximum operating speeds	13
5.2.3	Safety factors	13
5.2.4	Maximum operating speeds	13
5.2.5	Blotters	14
5.3	Requirements for non-precision cutting-off wheels	14
5.3.1	Bore tolerances	14
5.3.2	Sequence of maximum operating speeds	14
5.3.3	Safety factors	15
5.3.4	Maximum operating speeds	15
5.3.5	Requirements for the metal blank	16
5.3.6	Requirements for the connection of the superabrasive section to the metal blank	19
5.3.7	Tensioning of non-precision cutting-off wheels	21
5.3.8	Limitation of sides abrasives and/or superabrasives coating	21
5.4	Requirements for diamond wires	21
5.4.1	General	21
5.4.2	Requirements	21
5.4.3	Maximum operating speeds	22
5.5	Requirements for mounted points	22
5.5.1	Spindle diameter tolerances	22
5.5.2	Sequence of maximum operating speeds	22
5.5.3	Safety factors	22
5.6	Requirements for other superabrasive products for non-precision grinding	22
5.6.1	Bore diameter tolerances	22
5.6.2	Sequence of maximum operating speeds	22
5.6.3	Safety factors	22
5.6.4	Maximum operating speeds	23
5.6.5	Requirements for the connection of the abrasive section to the core	23
5.7	Marking	24
EN 13236:2010+A1:2015 (E) 6	Verification of the safety requirements	24

6.1	Verification of the general requirements	24
6.1.1	Visual inspection	24
6.1.2	Ring test	24
6.2	Verification of the strength requirements	24
6.2.1	Verification of the safety factor	24
6.2.2	Verification of the bending moment of non-precision cutting-off wheels	24
6.2.3	Verification of the strength requirements for other superabrasive products for non-precision grinding	27
6.2.4	Verification methods for diamond wires	28
6.3	Verification of marking	30
6.4	Verification of the requirements for blotters	30
6.5	Verification of tensioning of non-precision cutting-off wheels	30
7	Information for use	31
Annex A (normative) Marking		32
A.1	Content of the marking	32
A.1.1	Marking requirements	32
A.1.2	Additional inscriptions	34
A.1.3	Multiple or gang mounted wheels	34
A.2	Execution of the marking	35
Annex B (normative) Colour codes		36
Annex C (informative) Mounted points		37
C.1	Example of calculation of the maximum permissible speed of rotation	37
C.2	Example for the application of the calculation method	40
C.2.1	Types of mounted points	40
C.2.2	Assumptions for the calculation	41
C.2.3	Maximum permissible speeds of rotation	42
Annex D (normative) Reconditioning of cutting-off wheels according to 5.3.6.4		44
D.1	Preconditions for reconditioning	44
D.2	Additional marking requirements	44
Annex E (informative) Speed conversion table		46
Bibliography		49
Figures Figure 1 -- Position of cuts and openings in steel blanks		18
Figure 2 -- Example of cut-outs and openings		19
Figure 3 -- Segmented cutting-off wheels: Dimensions of segment height X1		25
Figure 4 -- Example of a bending test device for segmented cutting-off wheels		25
Figure 5 -- Cutting-off wheels with continuous rim: Dimensions of segment height X1		26
Figure 6 -- Example of a bending test device for cutting-off wheels with continuous rim		27
Figure 7 -- Example of a shearing force test device		28
Tables Table 1 -- Grinding method, type of machine, type of application		10
EN 13236:2010+A1:2015 (E) Table 2 -- Symbols		11
Table 3 -- Other symbols		12

Table 4 -- List of significant hazards	12
Table 5 -- Safety factors for precision superabrasive grinding and cutting-off wheels	13
Table 6 -- Maximum operating speeds as a function of the bond type	14
Table 7 -- Safety factors for non-precision cutting-off wheels	15
Table 8 -- Maximum operating speeds as a function of the bond type	15
Table 9 -- Dimensions of blanks for dry cutting-off	16
Table 10 -- Dimensions of blanks for wet cutting-off	17
Table 11 -- Bending strength b for cutting-off wheels for the use on hand-held cutting-off machines depending on segment height X_1 and segment length L_2	20
Table 12 -- Minimum bending moment M_b	20
Table 13 -- Safety factors for other superabrasive products for non-precision grinding	23
Table 14 -- Maximum operating speeds as a function of the bond type	23
Table A.1 -- Marking of superabrasive products	32
Table A.2 -- Restrictions of use (RE)	34
Table B.1 -- Colour codes and design of colour codes	36
Table C.1 -- Designation of the calculation quantities	39
Table C.2 -- Designation of mounted points	40
Table C.3 -- Characteristics for the calculation of maximum speeds of rotation	41
Table C.4 -- Mounted points, cylindrical shape, plain spindles (ZYN) vitrified bond (V)	42
Table C.5 -- Mounted points, cylindrical shape, reduced spindles (ZYA), vitrified bond (V)	42
Table C.6 -- Mounted points, cylindrical shape, plain spindle Schaft (ZYN), electroplated bond (G) ..	43
Table E.1 -- Speed conversion	46