

ISO/TS 13399-308:2016-02 (E)

Cutting tool data representation and exchange - Part 308: Creation and exchange of 3D models - Milling cutters with arbor hole for indexable inserts

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Starting elements, coordinate systems, planes	2
3.1	General	2
3.2	Reference system	2
3.3	Coordinate system at the cutting part	3
3.4	Planes	3
3.5	Design of the pocket seat and cutting reference point (CRP) of the insert	4
3.6	Adjustment coordinate system on workpiece side	7
3.6.1	General	7
3.6.2	Designation of the coordinate system workpiece side	8
4	Design of the model	9
4.1	General	9
4.2	Necessary parameters for the connection interface feature	10
4.3	Necessary properties for inserts	10
4.3.1	General	10
4.3.2	Properties for equilateral, equiangular and equilateral, nonequiangular inserts	10
4.3.3	Properties for nonequilateral, equiangular and nonequilateral, nonequiangular inserts	11
4.3.4	Design of the pocket seat feature	12
5	Face milling cutter	12
5.1	General	12
5.2	Necessary properties	13
5.3	Basic geometry	13
5.4	Determination of the position of the mounting coordinate system of insert	14
5.5	Chip flute and pocket seat	15
5.6	Face milling cutter, assembly	16
6	Shoulder milling cutter	17
6.1	General	17
6.2	Necessary properties	17
6.3	Basic geometry	17
6.4	Determination of the position of the mounting coordinate system of insert	17
6.5	Chip flute and pocket seat	18
6.6	Shoulder milling cutter, assembly	18
7	Plain milling cutter	19
7.1	General	19
7.2	Necessary properties	19
7.3	Basic geometry	20
7.4	Determination of the position of the mounting coordinate system of insert	20
7.5	Chip flute and pocket seat	21
7.6	Plain milling cutter, assembly	23

8	Shell milling cutter	23
8.1	General	23
8.2	Necessary properties	24
8.3	Basic geometry	24
8.4	Determination of the position of the mounting coordinate system of insert	25
8.5	Chip flute and pocket seat	25
8.6	Shell milling cutter, assembly	25
9	Full-side-slot milling cutter	25
9.1	General	25
9.2	Necessary properties	26
9.3	Basic geometry	26
9.4	Determination of the position of the mounting coordinate system of insert	27
9.5	Chip flute and pocket seat	28
9.6	Assembly of a full-side slot milling cutter	30
10	Half-side slot milling cutter	31
10.1	General	31
10.2	Necessary properties	31
10.3	Basic geometry	31
10.4	Determination of the position of the mounting coordinate system of insert	31
10.5	Chip flute and pocket seat	32
10.6	Half-side slot milling cutter, assembly	32
11	Full-side profile slot milling cutter	33
11.1	General	33
11.2	Necessary properties	33
11.3	Basic geometry	34
11.4	Determination of the position of the mounting coordinate system of insert	34
11.5	Chip flute and pocket seat	34
11.6	Full-side profile slot milling cutter, assembly	34
12	Full-side angular slot milling cutter	35
12.1	General	35
12.2	Necessary properties	35
12.3	Basic geometry	36
12.4	Determination of the position of the mounting coordinate system of insert	36
12.5	Chip flute and pocket seat	36
12.6	Full-side angular slot milling cutter, assembly	36
13	Saw blade/slitting cutter	36
13.1	General	36
13.2	Necessary properties	37
13.3	Basic geometry	37
13.4	Determination of the position of the mounting coordinate system of insert	38
13.5	Chip flute and pocket seat	40
13.6	Saw blade/slitting cutter, assembly	41
14	Design of details	42
14.1	Basics for modelling	42
14.2	Fixing threads for inserts	42
14.3	Contact surfaces/drive keys -- Orientation	42
14.4	Chamfers, roundings, others	42
15	Attributes of surfaces -- Visualization of the model features	42
16	Structure of the design elements (tree of model)	42
17	Data exchange model	43
	Annex A (informative) Information about nominal dimensions	45
	Bibliography	46