

# ISO/TS 13399-312:2016-02 (E)

## Cutting tool data representation and exchange - Part 312: Creation and exchange of 3D models - Reamers for indexable inserts

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vii
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Starting elements, coordinate systems, planes .....</b>	<b>2</b>
<b>3.1</b>	<b>General .....</b>	<b>2</b>
<b>3.2</b>	<b>Reference system .....</b>	<b>2</b>
<b>3.3</b>	<b>Primary coordinate system and mounting coordinate system .....</b>	<b>2</b>
<b>3.4</b>	<b>Coordinate system at the cutting part .....</b>	<b>3</b>
<b>3.5</b>	<b>Planes .....</b>	<b>3</b>
<b>3.6</b>	<b>Design of the pocket seat and cutting reference point (CRP) of the insert .....</b>	<b>4</b>
<b>3.7</b>	<b>Adjustment coordinate system on workpiece side .....</b>	<b>6</b>
<b>3.7.1</b>	<b>General .....</b>	<b>6</b>
<b>3.7.2</b>	<b>Designation of the coordinate system workpiece side .....</b>	<b>6</b>
<b>4</b>	<b>Design of the model .....</b>	<b>7</b>
<b>4.1</b>	<b>General .....</b>	<b>7</b>
<b>4.2</b>	<b>Necessary parameters for the connection interface feature .....</b>	<b>8</b>
<b>4.3</b>	<b>Necessary properties for inserts .....</b>	<b>8</b>
<b>4.3.1</b>	<b>General .....</b>	<b>8</b>
<b>4.3.2</b>	<b>Properties of inserts for reaming operations .....</b>	<b>9</b>
<b>4.3.3</b>	<b>Design of the pocket seat feature .....</b>	<b>9</b>
<b>5</b>	<b>Cylindrical reamer .....</b>	<b>9</b>
<b>5.1</b>	<b>General .....</b>	<b>9</b>
<b>5.2</b>	<b>Necessary properties .....</b>	<b>10</b>
<b>5.3</b>	<b>Basic geometry .....</b>	<b>11</b>
<b>5.4</b>	<b>Determination of the position of the mounting coordinate system of insert .....</b>	<b>11</b>
<b>5.5</b>	<b>Chip flute and pocket seat .....</b>	<b>12</b>
<b>5.6</b>	<b>Cylindrical reamer -- Assembly .....</b>	<b>13</b>
<b>6</b>	<b>Tapered reamer .....</b>	<b>14</b>
<b>6.1</b>	<b>General .....</b>	<b>14</b>
<b>6.2</b>	<b>Necessary properties .....</b>	<b>14</b>
<b>6.3</b>	<b>Basic geometry .....</b>	<b>15</b>
<b>6.4</b>	<b>Determination of the position of the mounting coordinate system of insert .....</b>	<b>15</b>
<b>6.5</b>	<b>Chip flute and pocket seat .....</b>	<b>16</b>
<b>6.6</b>	<b>Tapered reamer, assembled .....</b>	<b>17</b>
<b>7</b>	<b>Stepped(profile)reamer .....</b>	<b>17</b>
<b>7.1</b>	<b>General .....</b>	<b>17</b>
<b>7.2</b>	<b>Necessary properties .....</b>	<b>18</b>
<b>7.3</b>	<b>Basic geometry .....</b>	<b>19</b>
<b>7.4</b>	<b>Determination of the position of the mounting coordinate system of insert .....</b>	<b>20</b>
<b>7.5</b>	<b>Chip flute and pocket seat .....</b>	<b>21</b>
<b>7.6</b>	<b>Assembled stepped (profile) reamer .....</b>	<b>23</b>

8	<b>Bell style reamer .....</b>	<b>23</b>
8.1	<b>General .....</b>	<b>23</b>
8.2	<b>Necessary properties .....</b>	<b>24</b>
8.3	<b>Basic geometry .....</b>	<b>25</b>
8.4	<b>Determination of the position of the mounting coordinate system of insert .....</b>	<b>26</b>
8.5	<b>Chip flute and pocket seats .....</b>	<b>28</b>
8.6	<b>Assembled bell style reamer .....</b>	<b>29</b>
9	<b>Shell reamer .....</b>	<b>29</b>
9.1	<b>General .....</b>	<b>29</b>
9.2	<b>Necessary properties .....</b>	<b>30</b>
9.3	<b>Basic geometry .....</b>	<b>30</b>
9.4	<b>Determination of the position of the mounting coordinate system of insert .....</b>	<b>31</b>
9.5	<b>Chip flute and pocket seats .....</b>	<b>32</b>
9.6	<b>Assembled shell reamer .....</b>	<b>33</b>
10	<b>Design of details .....</b>	<b>34</b>
10.1	<b>Basics for modelling .....</b>	<b>34</b>
10.2	<b>Contact/clamping surfaces -- Orientation .....</b>	<b>34</b>
10.3	<b>Chamfers and roundings .....</b>	<b>35</b>
11	<b>Attributes of surfaces -- Visualization of the model features .....</b>	<b>35</b>
12	<b>Structure of the design elements (tree of model) .....</b>	<b>35</b>
13	<b>Data exchange model .....</b>	<b>36</b>
	<b>Annex A (informative) Information about nominal dimensions .....</b>	<b>38</b>
	<b>Bibliography .....</b>	<b>39</b>