

ISO 3365:2016-03 (E)

Indexable hardmetal (carbide) inserts with wiper edges, without fixing hole - Dimensions

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Types of inserts	1
4	Interchangeability	2
4.1	Tolerances	2
4.2	Dimensions m	2
5	Designation and marking	2
5.1	Designation	2
5.2	Marking	2
6	Measurement	2
7	Recommended dimensions	3
7.1	Triangular inserts	3
7.1.1	Symmetrical triangular inserts with 90° cutting edge angle, 11° normal clearance, and 11° wiper edge normal clearance	3
7.1.2	Asymmetrical triangular inserts with chamfered corners, 90° cutting edge angle, 11° normal clearance, and 15° wiper edge normal clearance	4
7.1.3	Asymmetrical triangular inserts with chamfered corners, 90° cutting edge angle, 20° normal clearance, and 20° wiper edge normal clearance	5
7.2	Square inserts	6
7.2.1	Symmetrical square inserts with chamfered corner, 75° cutting edge angle, 0° normal clearance, and 0° wiper edge normal clearance	6
7.2.2	Asymmetrical square inserts with chamfered corner, 75° cutting edge angle, 11° normal clearance, and 15° wiper edge normal clearance	7
7.2.3	Symmetrical square inserts with 45° cutting edge angle, 0° normal clearance, and 0° wiper edge normal clearance	8
7.2.4	Asymmetrical square inserts without chamfered corner, 75° cutting edge angle, 20° normal clearance, and 20° wiper edge normal clearance	9
Annex A (normative)	Tolerances for d, m, and s	10
Annex B (normative)	Method of measurement of "m" dimension	11
Annex C (normative)	Range of sizes for inserts with wiper edges, without fixation hole	12
Annex D (informative)	Relationship between designations in this International Standard and ISO 13399	14
Bibliography		15