ISO 3365:2016-03 (E)

Indexable hardmetal (carbide) inserts with wiper edges, without fixing hole - Dimensions

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Types of inserts 1

4 Interchangeability 2
4.1 Tolerances 2
4.2 Dimensions m 2

5 Designation and marking 2
5.1 Designation 2
5.2 Marking 2

6 Measurement 2

7 Recommended dimensions 3
7.1 Triangular inserts 3
7.1.1 Symmetrical triangular inserts with 90° cutting edge angle, 11° normal clearance, and 11° wiper edge normal clearance 3
7.1.2 Asymmetrical triangular inserts with chamfered corners, 90° cutting edge angle, 11° normal clearance, and 15° wiper edge normal clearance 4
7.1.3 Asymmetrical triangular inserts with chamfered corners, 90° cutting edge angle, 20° normal clearance, and 20° wiper edge normal clearance 5
7.2 Square inserts 6
7.2.1 Symmetrical square inserts with chamfered corner, 75° cutting edge angle, 0° normal clearance, and 0° wiper edge normal clearance 6
7.2.2 Asymmetrical square inserts with chamfered corner, 75° cutting edge angle, 11° normal clearance, and 15° wiper edge normal clearance 7
7.2.3 Symmetrical square inserts with 45° cutting edge angle, 0° normal clearance, and 0° wiper edge normal clearance 8
7.2.4 Asymmetrical square inserts without chamfered corner, 75° cutting edge angle, 20° normal clearance, and 20° wiper edge normal clearance 9

Annex A (normative) Tolerances for d, m, and s 10

Annex B (normative) Method of measurement of "m" dimension 11

Annex C (normative) Range of sizes for inserts with wiper edges, without fixation hole 12

Annex D (informative) Relationship between designations in this International Standard and ISO 13399 14

Bibliography 15