

# ISO/TS 13399-306:2018 (E)

## Cutting tool data representation and exchange — Part 306: Creation and exchange of 3D models — Drills and countersinking tools for indexable inserts

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Starting elements, coordinate systems, planes
4.1	General
4.2	Reference system (PCS — Primary coordinate system)
4.3	Coordinate system at the cutting part
4.4	Planes
4.5	Adjustment coordinate system on workpiece side
4.5.1	General
4.5.2	Designation of the coordinate system workpiece side
5	Design of the model
5.1	General
5.2	Necessary properties for inserts
5.2.1	General
5.2.2	Properties for equilateral, equiangular and equilateral, non-equiangular inserts
5.2.3	Properties for non-equilateral, equiangular and non-equilateral, non-equiangular inserts
5.2.4	Design of the pocket seat feature
6	Twist drill for indexable inserts (ISYC: 306-01)
6.1	General
6.2	Necessary properties
6.3	Basic geometry
6.4	Determination of the position of the mounting coordinate system of insert
6.5	Chip flute and pocket seat
6.6	Twist drill assembly
7	Step drill (ISYC: 306-02)
7.1	General
7.2	Necessary properties
7.3	Basic geometry
7.4	Determination of the position of the mounting coordinate system of insert
7.5	Chip flute and pocket seat
7.6	Step drill assembly
8	Core drill (ISYC: 306-03)
8.1	General
8.2	Necessary properties
8.3	Basic geometry
8.4	Determination of the position of the mounting coordinate system of insert
8.5	Chip flute and pocket seat
8.6	Core drill assembly
9	Face countersinking tool (ISYC: 306-04)

- 9.1 General
- 9.2 Necessary properties
- 9.3 Basic geometry
- 9.4 Determination of the position of the mounting coordinate system of insert
- 9.5 Chip flute and pocket seat
- 9.6 Face countersinking tool assembly
- 10 Step countersinking tool (ISYC: 306-05)
  - 10.1 General
  - 10.2 Necessary properties
  - 10.3 Basic geometry
  - 10.4 Determination of the position of the mounting coordinate system of insert
  - 10.5 Chip flute and pocket seat
  - 10.6 Step countersinking tool assembly
- 11 Trepanning drill (ISYC: 306-06)
  - 11.1 General
  - 11.2 Necessary properties
  - 11.3 Basic geometry
  - 11.4 Determination of the position of the mounting coordinate system of insert
  - 11.5 Chip flute and pocket seat
  - 11.6 Trepanning drill, assembled
- 12 Bell style countersinking tool (ISYC: 306-07)
  - 12.1 General
  - 12.2 Necessary properties
  - 12.3 Basic geometry
  - 12.4 Determination of the position of the mounting coordinate system of insert
  - 12.5 Chip flute and pocket seat
  - 12.6 Bell style countersinking tool, assembled
- 13 Reverse countersinking tool (ISYC: 306-08)
  - 13.1 General
  - 13.2 Necessary properties
  - 13.3 Basic geometry
  - 13.4 Determination of the position of the mounting coordinate system of insert
  - 13.5 Chip flute and pocket seat
  - 13.6 Assembled reverse countersinking tool
- 14 Step drill for adjustable solid drill (ISYC: 306-09)
  - 14.1 General
  - 14.2 Necessary properties
  - 14.3 Basic geometry
  - 14.4 Determination of the position of the mounting coordinate system of insert
  - 14.5 Chip flute and pocket seat
  - 14.6 Step drill for solid twist drills, assembly
- 15 Twist drills for drilling blades or drilling inserts (ISYC: 306-10)
  - 15.1 General
  - 15.2 Necessary properties
  - 15.3 Basic geometry
  - 15.4 Determination of the position of the mounting coordinate system of insert
  - 15.5 Chip flute and pocket seat
  - 15.6 Assembled twist drill for drilling blades or drilling inserts
- 16 Design of details
  - 16.1 Basis for modelling
  - 16.2 Fixing threads for inserts
  - 16.3 Contact/clamping surfaces – orientation
  - 16.4 Chamfers, roundings, others
- 17 Data exchange model

**Annex A (informative) Information about nominal dimensions**