DIN 1835-1:2024-03 (E)

Cylindrical shanks made of steel for machining tools - Part 1: Dimensions

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Dimensions and designation 4
4.1 General 4
4.2 Type A -- Plain cylindrical shank 4
4.4 Type D: Threaded cylindrical shank 8
4.5 Type E: Cylindrical shank with inclined clamping surface for connection dimensions 4.6 Type F: Cylindrical shank with a 90° conical fitting for cooling lubricant supply 11
4.6.1 General 11
4.6.2 Design A with central cooling lubricant supply 11
4.6.3 Design B with decentralized cooling lubricant supply with cooling channel connection 11
4.6.4 Design C with decentralized cooling lubricant supply with double cone 12

5 Design 13

Bibliography 14

Figures

Figure 1 — Type A: Plain cylindrical shank 5

Figure 2 — Type B: Single-flatted cylindrical shank (d_1 = 6 mm to 20 mm) 6

Figure 3 — Type B: Double-flatted cylindrical shank (d_1 = 25 mm to 63 mm) 7

Figure 4 — Type D: Threaded cylindrical shank 8

Figure 5 — Type E: Cylindrical shank with inclined clamping surface 10

Figure 6 — Type F, design A: Central cooling lubricant supply 11

Figure 7 — Type F, design B: Decentralized cooling lubricant supply with cooling channel connection 12

Figure 8 — Type F, design C: Decentralized cooling lubricant supply with double cone 12

Tables

Table 1 — Type A: Plain cylindrical shank, dimensions 5

Table 2 — Type B: Flatted cylindrical shank, dimensions 7

Table 3 — Type D: Threaded cylindrical shank, dimensions 9

Table 4 — Type E: Cylindrical shank with inclined clamping surface, dimensions 10

Table 5 — Type F: Cylindrical shank for MQL, dimensions 13