

# ISO 5686-1:2024-10 (E)

## Polygonal turret interface with flat contact surface - Part 1: Shanks of type F, H and A

| <b>Contents</b>  |   | <b>Page</b> |
|--|---|-------------|
| Foreword .....   |   | iv          |
| <b>1</b>   | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>   | <b>Normative references .....</b>                         | <b>1</b>    |
| <b>3</b>   | <b>Terms and definitions .....</b>                        | <b>1</b>    |
| <b>4</b>   | <b>Polygonal taper shanks, types and dimensions .....</b> | <b>2</b>    |
| <b>4.1</b>   | <b>General .....</b>                                      | <b>2</b>    |
| <b>4.2</b>   | <b>Polygonal taper shank, Type F .....</b>                | <b>3</b>    |
| <b>4.3</b>   | <b>Polygonal taper shank, Type H .....</b>                | <b>6</b>    |
| <b>4.4</b>   | <b>Polygonal taper shank, Type A .....</b>                | <b>7</b>    |
| <b>4.5</b>   | <b>Dimensions .....</b>                                   | <b>7</b>    |
| <b>5</b>   | <b>Design .....</b>                                       | <b>9</b>    |
| <b>5.1</b>   | <b>Fastening of the PTI tool holders .....</b>            | <b>9</b>    |
| <b>5.2</b>   | <b>Clamping forces .....</b>                              | <b>9</b>    |
| <b>5.3</b>   | <b>Material and heat treatment .....</b>                  | <b>9</b>    |
| <b>6</b>   | <b>Designation .....</b>                                  | <b>9</b>    |
| <b>Annex A (informative) Clamping forces for PTI shanks of types F, H and A .....</b>        |   | <b>10</b>   |
| <b>Annex B (informative) Measuring planes for contour determination of the polygon .....</b> |   | <b>11</b>   |
| <b>Annex C (informative) Application of PTI types in turret lathes .....</b>                 |   | <b>44</b>   |
| <b>Annex D (informative) Set-up and design of the PTI interface in turret lathes .....</b>   |   | <b>46</b>   |
| <b>Annex E (informative) Interface for energy and data transfer .....</b>                    |   | <b>49</b>   |
| <b>Bibliography .....</b>  |   | <b>50</b>   |