ISO 13942:2000-12 (E)

Bonded abrasive products - Limit deviations and run-out tolerances

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and designations 4

5 Straight grinding wheels, recessed, relieved and hubbed wheels 5
5.1 Types involved 5
5.2 Straight grinding wheels for general applications 6
5.3 Straight grinding wheels for special applications 8
5.4 Grinding wheels for high-pressure grinding 10
5.5 Straight grinding wheels used in sets 11
5.6 Cemented or clamped cylinder wheels and disc wheels 11

6 Dish and cup wheels 13
6.1 Types involved 13
6.2 Dish and cup wheels for general applications 14
6.3 Dish and cup wheels for tool grinding 14

7 Grinding wheels for cutting-off, deburring and fettling/snagging 14
7.1 Scope 14
7.2 Limit deviations TD of the outside diameter, axial run-out tolerance, TPL, and the radial run-out tolerance, TRL 15
7.3 Limit deviations TH of the hole diameter 16
7.4 Limit deviations TT and TU of the grinding wheel thickness 16

8 Segments 17

9 Cones and plugs with threaded insert 18

10 Honing stones and superfinishings 18

11 Hand finishing sticks 18