

ISO 16463:2004-06 (E)

Polycrystalline diamond inserts, tipped - Dimensions, types

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Insert shapes and design | 1 |
| 3.1 | Insert shapes | 1 |
| 3.2 | Normal clearance, n | 1 |
| 3.3 | Cutting edge corner | 1 |
| 3.4 | Tolerance class | 2 |
| 3.5 | Design of cutting edges | 2 |
| 3.6 | Insert type | 2 |
| 4 | Designation | 2 |
| 4.1 | General | 2 |
| 4.2 | Designation of a tipped insert for turning | 2 |
| 4.3 | Designation of a tipped insert for milling | 2 |
| 5 | Dimensions | 2 |
| 5.1 | Insert shape T with fixing hole (inserts for turning) | 2 |
| 5.2 | Insert shape T without fixing hole (inserts for turning) | 4 |
| 5.3 | Insert shape S with fixing hole (inserts for turning) | 5 |
| 5.4 | Insert shape S without fixing hole (inserts for turning) | 5 |
| 5.5 | Insert shape C with fixing hole (inserts for turning) | 6 |
| 5.6 | Insert shape D with fixing hole (inserts for turning) | 8 |
| 5.7 | Insert shape V with fixing hole (inserts for turning) | 9 |
| 5.8 | Insert shape S with fixing hole (inserts for milling) | 10 |
| 5.9 | Insert shape C with fixing hole (inserts for milling) | 11 |
| 5.10 | Insert shape W with fixing hole (inserts for turning) | 12 |
| 6 | Cutting edge length, l₁, of tipped inserts | 13 |
| 6.1 | General | 13 |
| 6.2 | Inserts with radius | 13 |
| 6.3 | Inserts with wiper edge | 13 |
| 7 | Base material, cutting material | 14 |
| 8 | Measurements | 14 |
| 9 | Marking | 14 |