

DIN EN 12680-3:2026-03 (E)

Founding - Ultrasonic testing - Part 3: Spheroidal graphite cast iron castings

| Contents | | Page |
|--|--|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Requirements | 5 |
| 4.1 | Order information | 5 |
| 4.2 | Extent of testing | 5 |
| 4.3 | Wall section zones | 5 |
| 4.4 | Maximum acceptable size of discontinuities | 6 |
| 4.5 | Qualification of personnel | 6 |
| 4.6 | Severity levels | 6 |
| 5 | Testing | 6 |
| 5.1 | Principles | 6 |
| 5.2 | Material | 6 |
| 5.3 | Equipment and coupling medium | 6 |
| 5.3.1 | Ultrasonic instrument | 6 |
| 5.3.2 | Probes | 7 |
| 5.3.3 | Checking of the ultrasonic test equipment | 8 |
| 5.3.4 | Coupling medium | 8 |
| 5.3.5 | Time base range and sensitivity setting of the ultrasonic test equipment | 8 |
| 5.3.6 | Detection sensitivity | 9 |
| 5.4 | Preparation of casting surfaces for testing | 9 |
| 5.5 | Test procedure | 9 |
| 5.5.1 | General | 9 |
| 5.5.2 | Sensitivity setting | 9 |
| 5.5.3 | Consideration of various types of indications | 10 |
| 5.5.4 | Evaluation and recording of indications | 10 |
| 5.5.5 | Assessment of discontinuities to be recorded | 10 |
| 5.5.6 | Characterization and sizing of discontinuities | 10 |
| 5.6 | Test report | 11 |
| Annex A (informative) Significant technical changes between this document and the previous edition | | 21 |
| Bibliography | | 23 |