

ISO 23210:2009-08 (E)

Stationary source emissions - Determination of PM<(Index)10>/PM<(Index)2,5> mass concentration in flue gas - Measurement at low concentrations by use of impactors

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols and abbreviated terms | 3 |
| 5 | Principle of the method | 5 |
| 6 | Specification of the two-stage impactor | 8 |
| 7 | Sampling train | 11 |
| 8 | Preparation, measurement procedure and post-treatment | 13 |
| 9 | Calculation of the results | 17 |
| 10 | Performance characteristics | 17 |
| 11 | Reporting | 20 |
| Annex A (normative) Calculation of the sample volumetric flow rate of the impactor | | 21 |
| Annex B (informative) General equations concerning impaction theory | | 28 |
| Annex C (informative) Results of method validation | | 30 |
| Annex D (informative) Influence of variations in the flue gas temperature and flue gas composition on the Reynolds number | | 36 |
| Annex E (informative) Entry nozzle | | 38 |
| Annex F (informative) Equipment list | | 39 |
| Annex G (normative) Determination of a representative sampling point | | 41 |
| Bibliography | | 42 |