

ISO 16000-24:2009-12 (E)

Indoor air - Part 24: Performance test for evaluating the reduction of volatile organic compound (except formaldehyde) concentrations by sorptive building materials

| Contents | | Page |
|--|---|-------------|
| Foreword | | iv |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols | 4 |
| 5 | Principle | 4 |
| 6 | Apparatus and materials | 5 |
| 7 | Test conditions | 6 |
| 7.1 | General | 6 |
| 7.2 | Test conditions for concentration reduction performance determination | 7 |
| 7.3 | Factors affecting the concentration reduction performance | 8 |
| 8 | Verification of test conditions | 8 |
| 8.1 | Monitoring of test conditions | 8 |
| 8.2 | Air-tightness of test chamber | 8 |
| 8.3 | Air change rate in test chamber | 9 |
| 8.4 | Efficiency of the internal test chamber air mixing | 9 |
| 8.5 | Recovery | 9 |
| 9 | Preparation of test chamber | 9 |
| 10 | Preparation of test specimens | 9 |
| 11 | Test methods | 9 |
| 11.1 | Background concentration and spiked supply air | 9 |
| 11.2 | Placing the test specimen in the test chamber | 10 |
| 11.3 | Time intervals for measurement of chamber concentration | 10 |
| 11.4 | Air sampling | 10 |
| 12 | Determination of target compounds | 11 |
| 13 | Expression of results | 11 |
| 13.1 | Calculation of sorption flux | 11 |
| 13.2 | Calculation of equivalent ventilation rate per area | 11 |
| 13.3 | Calculation of total mass per area of sorption and saturation mass per area | 11 |
| 14 | Test report | 12 |
| Annex A (normative) Sample tube test for long-term reduction performance | | 14 |
| Annex B (normative) System for quality assurance and quality control | | 18 |
| Bibliography | | 20 |