

ISO 12219-3:2012-06 (E)

Interior air of road vehicles - Part 3: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Micro-scale chamber method

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Principle	2
5	Apparatus	2
6	Test conditions	3
6.1	Temperature	4
6.2	Air or gas flow rate through the micro-scale chamber	4
6.3	Quality of supplied air or gas and background concentration of organic vapours	4
6.4	Control measures	4
7	Test specimens	4
7.1	General	4
7.2	Preparation of the test specimen	5
8	Cleaning micro-scale chamber components	5
9	Test method	5
9.1	Sampling media	5
9.2	Measuring background concentrations	6
9.3	Vapour sampling	6
9.4	Sealing the vapour sampling devices after gas sample collection	6
9.5	Analysis of vapour sampling devices	6
9.6	Storage of the test specimen between emissions tests (if required)	6
9.7	Cleaning the micro-scale chamber after use	6
10	Calculation of vapour concentrations and specific emission rates	7
11	Test report	8
12	Quality assurance/quality control	9
Annex A (informative) Micro-scale chamber principles		10
Annex B (informative) Micro-scale chamber -- Example 1		12
Annex C (informative) Micro-scale chamber -- Example 2		14
Annex D (informative) Micro-scale chamber -- Example 3		16

Annex E (informative) Assessment of VOC recoveries	18
Annex F (informative) Calculation of specific emission rates from micro-scale chamber air concentration	19
Bibliography	21