

# ISO 13271:2012-06 (E)

## Stationary source emissions - Determination of PM10/PM2,5 mass concentration in flue gas - Measurement at higher concentrations by use of virtual impactors

---

| <b>Contents</b>   |   | <b>Page</b> |
|---|---|-------------|
| Foreword .....  |   | iv          |
| Introduction .....  |   | v           |
| 1   | Scope .....   | 1           |
| 2   | Normative references .....                                  | 1           |
| 3   | Terms and definitions .....                                 | 1           |
| 4   | Symbols and abbreviated terms .....                         | 4           |
| 4.1   | Symbols .....   | 4           |
| 4.2   | Abbreviated terms .....                                     | 5           |
| 5   | Principle .....   | 6           |
| 5.1   | General .....   | 6           |
| 5.2   | Theory of virtual impactor .....                            | 6           |
| 6   | Specification of the two-stage virtual impactor .....       | 8           |
| 6.1   | General .....   | 8           |
| 6.2   | Separation curves .....                                     | 8           |
| 6.3   | Verification of the separation curves .....                 | 9           |
| 6.4   | Operating conditions .....                                  | 9           |
| 7   | Sampling train .....  | 12          |
| 7.1   | Measuring setup .....                                       | 12          |
| 7.2   | Equipment and working materials .....                       | 13          |
| 8   | Preparation, measurement procedure and post-treatment ..... | 15          |
| 8.1   | General .....   | 15          |
| 8.2   | Pre-treatment .....   | 15          |
| 8.3   | Measurement procedure .....                                 | 16          |
| 8.4   | Weighing procedure .....                                    | 17          |
| 8.5   | Post-sampling treatment of weighed parts .....              | 18          |
| 9   | Calculation of the results .....                            | 18          |
| 10  | Performance characteristics .....                           | 19          |
| 10.1  | Virtual impactor load .....                                 | 19          |
| 10.2  | Detection limit .....                                       | 19          |
| 10.3  | Measurement uncertainty .....                               | 19          |
| 10.4  | Particle losses .....                                       | 19          |
| 11  | Test report .....   | 20          |
| Annex A (informative) Physical property estimation for the calculation of sample volume flow rate ..... |   | 21          |
| Annex B (informative) Errors by deviations from isokinetic sampling .....                               |   | 25          |
| Annex C (informative) Example of a two-stage virtual impactor .....                                     |   | 27          |

|  |           |
|--|-----------|
| <b>Annex D (informative) Influence of variations in the flue gas temperature and flue gas composition on the Reynolds number .....</b> | <b>31</b> |
| <b>Annex E (informative) Entry nozzle .....</b>  | <b>34</b> |
| <b>Annex F (informative) Equipment list .....</b>  | <b>35</b> |
| <b>Annex G (normative) Determination of a representative sampling point .....</b>  | <b>37</b> |
| <b>Annex H (informative) Generation of standard aerosol for virtual impactor calibration .....</b>                                     | <b>39</b> |
| <b>Bibliography .....</b>  | <b>40</b> |