

DIN ISO 12219-3:2013-12 (E)

Interior air of road vehicles - Part 3: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Micro-scale chamber method (ISO 12219-3:2012)

| Contents | | Page |
|--|--|-------------|
| National foreword | | 3 |
| National Annex NA (informative) Bibliography | | 5 |
| Introduction | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 9 |
| 4 | Principle | 9 |
| 5 | Apparatus | 9 |
| 6 | Test conditions | 10 |
| 6.1 | Temperature | 11 |
| 6.2 | Air or gas flow rate through the micro-scale chamber | 11 |
| 6.3 | Quality of supplied air or gas and background concentration of organic vapours | 11 |
| 6.4 | Control measures | 11 |
| 7 | Test specimens | 11 |
| 7.1 | General | 11 |
| 7.2 | Preparation of the test specimen | 12 |
| 8 | Cleaning micro-scale chamber components | 12 |
| 9 | Test method | 12 |
| 9.1 | Sampling media | 12 |
| 9.2 | Measuring background concentrations | 13 |
| 9.3 | Vapour sampling | 13 |
| 9.4 | Sealing the vapour sampling devices after gas sample collection | 13 |
| 9.5 | Analysis of vapour sampling devices | 13 |
| 9.6 | Storage of the test specimen between emissions tests (if required) | 13 |
| 9.7 | Cleaning the micro-scale chamber after use | 13 |
| 10 | Calculation of vapour concentrations and specific emission rates | 14 |
| 11 | Test report | 15 |
| 12 | Quality assurance/quality control | 16 |
| Annex A (informative) Micro-scale chamber principles | | 17 |
| Annex B (informative) Micro-scale chamber -- Example 1 | | 19 |
| Annex C (informative) Micro-scale chamber -- Example 2 | | 21 |

| | |
|--|-----------|
| Annex D (informative) Micro-scale chamber -- Example 3 | 23 |
| Annex E (informative) Assessment of VOC recoveries | 25 |
| Annex F (informative) Calculation of specific emission rates from micro-scale chamber air concentration | 26 |
| Bibliography | 28 |